CONSTRUCTION DOCUMENTS STAR COMMUNICATIONS NEW HEADQUARTERS CLINTON, NC

<u>VOLUME 1</u>

- T1.1 TITLE SHEET VOLUME 1 SURVEY OF PROPERTY (ATLANTIC SURVEYING)
- CO.O COVER SHEET
- CO.1 EXISTING CONDITION PLAN AND DEMOLITION PLAN
- C1.1 SITE OVERALL C1.11 SITE PLAN - SOUTH
- C1.12 SITE PLAN NORTH
- C2.11 UTILITIES PLAN SOUTH
- C2.12 UTILITIES PLAN NORTH
- C3.11 GRADING AND STORM DRAINAGE PLAN SOUTH
- C3.12 GRADING AND STORM DRAINAGE PLAN NORTH C4.11 EROSION CONTROL PLAN - PHI
- C4.12 EROSION CONTROL PLAN PH2
- C5.1 SITE DETAILS
- C5.2 SITE DETAILS
- C5.3 WATER DETAILS
- C5.4 SEWER AND STORM DETAILS
- CG.1 EROSION CONTROL NOTES AND CALCULATIONS CG.2 EROSION CONTROL NOTES - NCGO1
- CG.3 EROSION CONTROL DETAILS
- L1.11 LANDSCAPE PLAN SOUTH
- L2.11 LANDSCAPE NOTES AND DETAILS

<u>STRUCTURAL</u> ARCHITECTURAL SO.1 GENERAL NOTES TI.2 TITLE SHEET VOLUME 2 BUILDING CODE ANALYSIS, LEGENDS, SYMBOLS, 50.2 GENERAL NOTES AND ABBREVIATIONS BC1.1 SI.11 FOUNDATION PLAN - WEST AND ABBREVIATIONS ASP1.0 CAMPUS SITE PLAN S1.12 FOUNDATION PLAN - EAST 52.11 SECOND FLOOR FRAMING PLAN - WEST ASP1.1 PARTIAL SITE PLAN A1.1 OVERALL FIRST FLOOR PLAN 52.12 SECOND FLOOR FRAMING PLAN - EAST 53.11 ROOF FRAMING PLAN - WEST A].]] PARTIAL FIRST FLOOR PLAN - WEST 53.12 ROOF FRAMING PLAN - EAST A1.12 PARTIAL FIRST FLOOR PLAN - EAST OVERALL SECOND FLOOR PLAN 54.1 SECTIONS AND DETAILS A1.2 PARTIAL SECOND FLOOR PLAN - WEST 54.2 SECTIONS A1.21 54.3 SECTIONS A1.22 PARTIAL SECOND FLOOR PLAN - EAST 54.4 SECTIONS OVERALL ROOF PLAN A1.3 54.5 SECTIONS A1.31 PARTIAL ROOF PLAN - WEST PARTIAL ROOF PLAN - EAST 55.1 TYPICAL DETAILS A1.32 55.2 TYPICAL DETAILS BUILDING ELEVATIONS A2.0 55.3 TYPICAL DETAILS A2.1 **BUILDING ELEVATIONS** 55.4 TYPICAL DETAILS A2.2 BUILDING ELEVATIONS A2.3 BUILDING SECTIONS BUILDING SECTIONS A2.4 A2.5 BUILDING SECTIONS A3.1 WALL SECTIONS A3.2 WALL SECTIONS WALL SECTIONS A3.3 A3.4 WALL SECTIONS A4.1 ENLARGED FLOOR PLANS A4.2 ENLARGED FLOOR PLANS INTERIOR ELEVATIONS A4.3 INTERIOR ELEVATIONS A4.4 A4.5 STAIR ELEVATIONS A5.1 OVERALL FIRST FLOOR REFLECTED CEILING PLAN A5.11 FIRST FLOOR REFLECTED CEILING PLAN - WEST A5.12 FIRST FLOOR REFLECTED CEILING PLAN - EAST A5.2 OVERALL SECOND FLOOR REFLECTED CEILING PLAN SECOND FLOOR REFLECTED CEILING PLAN - WEST A5.21 SECOND FLOOR REFLECTED CEILING PLAN - EAST A5.22 AG.1 EXTERIOR DETAILS A6.2 EXTERIOR DETAILS EXTERIOR DETAILS A6.3 WALL TYPES A7.1 A7.2 INTERIOR DETAILS A7.3 INTERIOR DETAILS INTERIOR DETAILS A7.4 A7.5 STAIR/ELEVATOR DETAILS A8.1 DOOR SCHEDULE A8.2 WINDOW SCHEDULE AND DETAILS CURTAINWALL ELEVATIONS AND DETAILS A8.3 A8.4 DOOR DETAILS

<u>VOLUME 2</u>

JKF PROJECT NO. 2022-17

)LUME 1

JULY 15, 2023



JKF ARCHITECTURE, P.C. 625 LYNNDALE CT., SUITE F GREENVILLE, NC 27858 (252)355-1068





RIVERS & ASSOCIATES, INC. CIVIL ENGINEERS 107 EAST SECOND STREET GREENVILLE, NC 27858 252-752-4135

NESER & ROOMSBURG, PA STRUCTURAL ENGINEERS 748 LORD DUNMORE DRIVE, STE. 101 VIRGINIA BEACH, VA 23464 757-474-0612

VOLUME 3 FIRE PROTECTION T1.3 TITLE SHEET VOLUME 3 FPO.1 FIRE PROTECTION, NOTES, LEGEND AND DETAILS FPO.2 OVERALL FIRE PROTECTION SITE PLAN FP1.11 FIRST FLOOR FIRE PROTECTION HEAD PLAN - WEST FP1.12 FIRST FLOOR FIRE PROTECTION HEAD PLAN - EAST FP1.21 SECOND FLOOR FIRE PROTECTION HEAD PLAN - WEST FP1.22 SECOND FLOOR FIRE PROTECTION HEAD PLAN - EAST PLUMBING P1.1 PLUMBING FIRST - FLOOR PLAN P1.11 PLUMBING FIRST FLOOR - WEST P1.12 PLUMBING FIRST FLOOR - EAST P1.2 PLUMBING SECOND - FLOOR PLAN P1.21 PLUMBING SECOND FLOOR - WEST P1.22 PLUMBING SECOND FLOOR - EAST P1.3 PLUMBING ROOF PLAN P1.31 PLUMBING ROOF PLAN - WEST P1.32 PLUMBING ROOF PLAN - EAST P2.1 ENLARGED PLUMBING PLANS P2.2 ENLARGED PLUMBING PLANS P3.1 WATER PIPING RISER P4.1 PLUMBING FIXTURE SCHEDULE P4.2 PLUMBING FIXTURE SCHEDULE AND DETAILS P4.3 PLUMBING FIXTURE SCHEDULE P4.4 PLUMBING NOTES, LEGEND, LOAD, AND DETAILS MECHANICAL MI.1 OVERALL FIRST FLOOR MECHANICAL PLAN M1.11 OFFICE BUILDING FIRST FLOOR MECHANICAL PLAN - WEST M1.12 OFFICE BUILDING FIRST FLOOR MECHANICAL PLAN - EAST MI.2 OVERALL SECOND FLOOR MECHANICAL PLAN M1.21 OFFICE BUILDING SECOND FLOOR MECHANICAL PLAN - WEST MI.22 OFFICE BUILDING SECOND FLOOR MECHANICAL PLAN - EAST M2.1 MECHANICAL SCHEDULE M2.2 MECHANICAL NOTES, LEGEND AND DETAILS M3.1 MECHANICAL DETAILS VRF INFORMATION M4.1 M4.2 VRF INFORMATION

ATLANTEC ENGINEERS, PA PLUMBING, MECHANICAL & ELECTRICAL ENGINEERS 3221 BLUE RIDGE ROAD, SUITE 113 RALEIGH, NC 27612 919-571-1111


M4.3 VRF INFORMATION

ELECTRICAL

- E1.0 OVERALL SITE ELECTRICAL PLAN
- E1.1 FIRST FLOOR PLAN
- E1.11 OFFICE BUILDING FIRST FLOOR LIGHTING PLAN WEST E1.12 OFFICE BUILDING FIRST FLOOR LIGHTING PLAN - EAST
- E1.2 OFFICE BUILDING SECOND FLOOR LIGHTING PLAN WEST
- E1.21 SECOND FLOOR PLAN
- E1.22 OFFICE BUILDING SECOND FLOOR LIGHTING PLAN EAST
- E2.11 OFFICE BUILDING FIRST FLOOR POWER PLAN WEST E2.12 OFFICE BUILDING FIRST FLOOR POWER PLAN - EAST
- E2.21 OFFICE BUILDING SECOND FLOOR POWER PLAN WEST
- E2.22 OFFICE BUILDING SECOND FLOOR POWER PLAN EAST
- E3.11 OFFICE BUILDING FIRST FLOOR HVAC POWER PLAN WEST E3.12 OFFICE BUILDING FIRST FLOOR HVAC POWER PLAN - EAST
- E3.21 OFFICE BUILDING SECOND FLOOR HVAC POWER PLAN WEST E3.22 OFFICE BUILDING SECOND FLOOR HVAC POWER PLAN - EAST
- E4.1 OFFICE BUILDING POWER RISER PANEL SCHEDULE E4.2 PANEL SCHEDULE

E4.3 PANEL SCHEDULE

- E5.1 OFFICE BUILDING LEGEND, NOTES, DETAILS AND FIXTURES E5.2 DETAILS
- E5.3 OFFICE BUILDING FIXTURE SCHEDULE
- FIRE ALARM
- FA1.0 OVERALL FIRE ALARM
- FA1.1 FIRST FLOOR PLAN
- FA1.11 FIRST FLOOR FIRE ALARM PLAN WEST FA1.12 FIRST FLOOR FIRE ALARM PLAN - EAST
- FA1.2 SECOND FLOOR PLAN
- FA1.21 SECOND FLOOR FIRE ALARM PLAN WEST
- FA1.22 SECOND FLOOR FIRE ALARM PLAN EAST
- FA2.1 FIRE ALARM RISER, LEGEND, NOTES, DETAILS AND MATRIX
- FA2.2 BDA DETAIL FIRE ALARM DEVICE MOUNTING DETAIL






Image: Is (100 Period Area Sections) BUTEFINITION: Interment Mode Interment Mode BUTEFINITION: Interment Mode Interment Mode Interment Mode	L		STA	·····
1 Image: Section and	K			
1 Image: Section and	J			
G Image: Contraction Additional Contract in Additional Contract International International Contract International International Conterect International Contrec	Н	MUNICIPALITY: NC PIN:	STAR TELEPHONE MEMBERSHIP CORPORATION 1322 SUNSET AVE City of Clinton 12104280001	
r Lot Tracks Strate	G	ZONING: ADJACENT ZONING: PROPOSED USE: PROPOSED GROSS FLOOR AREA:	HC - Planned Industrial HC - Planned Industrial RA-20 - Residential Agriculture RA - Rural and Agriculture (Sampson County ETJ) OFFICE 29313 SF	
E BENEFRAL NOTES: D BENEFRAL NOTES: 1 CONTRACTOR MUST NOTES NOTICIDATE DIMENSIONED ALL CENTER, INC. (INC 811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES INCLUDE TO TOTAL 18 D BENEFRAL NOTES: 1 CONTRACTOR MUST NOTES NOTICI CARDINA ONE CALL CENTER, INC. (INC 811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES INCLUDE TO TOTAL 18 D BENEFRAL NOTES: 1 CONTRACTOR MUST NOTES NORTH CARDINA ONE CALL CENTER, INC. (INC 811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES INCLUDE TO TOTAL 18 1 CONTRACTOR MUST NOTES NORTH CARDINA ONE CALL CENTER, INC. (INC 811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES INCLUDE TO TOTAL 18 1 CONTRACTOR MUST NOTES NORTH CARDINA DUTILITIES LOCATED PRIOR TO EXCAVATING OR TRENCHING. 2 ELECTRIC CAN TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. 3 ALL REQUIRED IMPROVEMENTS SHALL BE INSTALLED UNDERGROUND. 4 ELECTRIC CAN TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. 5 THIS SITE IN OT LOCATED IN A 200K SY (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUARY SEWER AND STORM DRAIMAGE SYSTEMS. 6 FROSION CONTROL PIAN APPRICABLE RUID DING CODES. SUPE SHALL MARET ALL RELATIVE NORTH CARDINA ACCESSIBUITY 7 INSUMARSE RAND MARY SEVERE AND	F	LOT AREA: EXISTING IMPERVIOUS: BUILDING (ROOF): ASPHALT AND C&G 5' GRAVEL TRAIL CONCRETE: TOTAL IMPERVIOUS: LOT COVERAGE:	3,412 SF 29,851 SF 108,807 SF 13,522 SF 8,690 SF 160,870 SF 32.1%	
B GENERAL NOTES: CONTRACTOR MUST NOTIFY NORTH CAROLINA ONE-CALL CENTER, INC. (NC-811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES CONTRACTOR MUST NOTIFY NORTH CAROLINA ONE-CALL CENTER, INC. (NC-811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES CONTRACTOR MUST NOTIFY NORTH CAROLINA ONE-CALL CENTER, INC. (NC-811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES CONTRACTOR MUST NOTIFY NORTH CAROLINA ONE-CALL CENTER, INC. (NC-811) AT LEAST 72 HOURS PRIOR TO THE START OF 13. ACCESS TO PUBLIC UTILITIES CONTRACTOR MUST NOT O HAVE ALL UNDERGROUND. CELECTRIC AND TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. ALL REQUIRED IMPROVEMENTS SHALL COMPLY WITH THE CITY OF CLINTON STANDARD AND DETAILS. CONSTRUCTION PLAN APPROVAL FROM CITY OF CLINTON STANDARD AND DETAILS. CONSTRUCTION PLAN APPROVAL FROM CITY OF CLINTON STANDARD AND DETAILS. STEEMS. THIS SITE IS NOT LOCATED IN A ZONE 'Y' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS INFORMANCE RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. THIS SITE DOES NOT RECTAIL BAPPROVAL RADE PROVER RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. THIS SITE DOES NOT RECTAIL APPROVAL REQUIRED. EROSION CONTROL PLAN APPROVAL REQUIRED. ENDILDINGS MUST MEET ALL APPLICABLE BUILDING CODES. SITE SHALL MEET ALL RELATIVE NORTH CAROLINA ACCESSIBILITY NEW BUILDINGS MUST MEET ALL APPLICABLE BUILDING CODES. SITE SHALL MEET ALL RELATIVE NORTH CAROLINA ACCESSIBILITY NEW BUILDINGS MUST MEET ALL APPLICABLE BUILDING CODES. SITE SHALL MEET ALL RELATIVE NORTH CAROLINA ACCESSIBILITY	E	FRONT SIDE REAR BUFFERYARD PARKING SUMMARY	15 ft 15 ft (10ft Parking Area Setback) 15 ft (10ft Parking Area Setback) Minimum / Notes 15' wide evergreen bufferyard per City of Clinton, NC Land Development Ordinance Section 8.2 Buffers	
C CONTRACTOR MUST NOTIFY NORTH CAROLINA ONE-CALL CENTER, INC. (NC-811) AT LEAST 72 HOURS PRIOR TO THE START OF ACCESS TO PUBLIC UTILITIES SUCCESSION OF THE START OF ACCESS TO PUBLIC UTILITIES SUCCESSION OF THE START OF ACCESS TO PUBLIC UTILITIES SUCCESSION OF THE START OF ELECTRIC AND TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. ELECTRIC AND TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. ALL REQUIRED IMPROVEMENTS SHALL COMPLY WITH THE CITY OF CLINTON STANDARD AND DETAILS. CONSTRUCTION PLAN APPROVAL FROM CITY OF CLINTON STANDARD AND DETAILS. SHALL BE OBTAINED PRIOR TO CONSTRUCTION OF ANY STREET, WATER, AND/OR SANITARY SEWER AND STORM DRAINAGE SYSTEMS. THIS SITE IS NOT LOCATED IN A ZONE 'X' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS IDENTIFIED BY FEMA FLOOD INSURANCE RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. THIS SITE IS NOT LOCATED IN A ZONE 'X' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS IDENTIFIED BY FEMA FLOOD INSURANCE RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. THIS SITE IS NOT LOCATED IN A ZONE 'X' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS IDENTIFIED BY FEMA FLOOD INSURANCE RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. EROSION CONTROL PLAN APPROVAL REQUIRED. EROSION CONTROL PLAN APPROVAL REQUIRED. BUILDINGS MUST MEET ALL APPLICABLE BUILDING CODES. SITE SHALL MEET ALL RELATIVE NORTH CAROLINA ACCESSIBILITY COST RECONDANCE WITH THE CLOSURES ANTER AND AND THE CLOSURES AND MUST BE ACCORDANCE WITH THE CLOSURES ON THE CONTRACTOR. NEW BUILDINGS MUST OF ALL SITE LIGHTING SHALL BE PROVIDED BY PRIVATE CONTRACTOR.	D		140 10 HC 108=TOTAL 148	S
14. ELECTRIC AND TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. 14. ELECTRIC EASEMENT IS . 2. ELECTRIC AND TELEPHONE UTILITIES SHALL BE INSTALLED UNDERGROUND. 15. NO BUILDINGS, STRUCTO 3. ALL REQUIRED IMPROVEMENTS SHALL COMPLY WITH THE CITY OF CLINTON STANDARD AND DETAILS. 15. NO BUILDINGS, STRUCTO 4. CONSTRUCTION PLAN APPROVAL FROM CITY OF CLINTON STANDARD AND DETAILS. 16. THIS SITE SIDE OF CONSTRUCTION OF ANY STREET, WATER, AND/OR SANITARY SEWER AND STORM DRAINAGE 16. 5. THIS SITE IS NOT LOCATED IN A ZONE 'X' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS 16. THIS SITE DOES NOT RECEPTACLES AND IMPE APPROVAL, AS APPROPE 6. EROSION CONTROL PLAN APPROVAL REQUIRED. 17. LANE CLOSURES ON THE AND DETAILS. 17. LANE CLOSURES ON THE AND DETAILS. 7. BUILDINGS MUST MEET ALL APPLICABLE BUILDING CODES. SITE SHALL MEET ALL RELATIVE NORTH CAROLINA ACCESSIBILITY 17. LANE CLOSURES AND MUST BE CLOSURES AND MUST BE CLOSURES ON THE CLOSURES ON THE CLOSURES ON HOLIDAYS ACCORDANCE WITH TH CLOSURES ON THE CLOSURES ON THE CLOSURES ON THE CLOSURES ON THE CLOSURES AND MUST BE CLOSURES ON PROVAL REQUIRED. 18. ALL SITE LIGHTING SHALL 8. NCDOT AND DRIVEWAY PERMITS ARE REQUIRED. 19. NEW BUILDINGS MUST OF CLOSURES OTHERWISE NOTED. 19. 9. REFUSE COLLECTION		1. CONTRACTOR MUST NOTIFY NOR		13. ACCESS TO PUBLIC UTILITIES N
5. THIS SITE IS NOT LOCATED IN A ZONE 'X' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS 17. LANE CLOSURES ON THO B 16. EROSION CONTROL PLAN APPROVAL REQUIRED. 17. LANE CLOSURES ON HOLIDAYS B 7. BUILDINGS MUST MEET ALL APPLICABLE BUILDING CODES. SITE SHALL MEET ALL RELATIVE NORTH CAROLINA ACCESSIBILITY 18. ALL SITE LIGHTING SHALL 8. NCDOT AND DRIVEWAY PERMITS ARE REQUIRED. 19. NEW BUILDINGS MUST OF 9. REFUSE COLLECTION SHALL BE PROVIDED BY PRIVATE CONTRACTOR. 19. NEW BUILDINGS MUST OF 10. ALL DIMENSIONS ARE TO BACK OF CURB UNLESS OTHERWISE NOTED. NOTED.	С	 2. ELECTRIC AND TELEPHONE UTILIT 3. ALL REQUIRED IMPROVEMENTS S 4. CONSTRUCTION PLAN APPROVAL SHALL BE OBTAINED PRIOR TO CO. 	IES SHALL BE INSTALLED UNDERGROUND. HALL COMPLY WITH THE CITY OF CLINTON STANDARD AND DETAILS. FROM CITY OF CLINTON STANDARD AND DETAILS.	 ELECTRIC EASEMENT IS 10' IN NO BUILDINGS, STRUCTURES PRINCIPLE AND ACCESSORY S MECHANICAL EQUIPMENT, C RECEPTACLES AND IMPERVIC APPROVAL, AS APPROPRIATE
 8. NCDOT AND DRIVEWAY PERMITS ARE REQUIRED. 9. REFUSE COLLECTION SHALL BE PROVIDED BY PRIVATE CONTRACTOR. 10. ALL DIMENSIONS ARE TO BACK OF CURB UNLESS OTHERWISE NOTED. 	B	 THIS SITE IS NOT LOCATED IN A ZO IDENTIFIED BY FEMA FLOOD INSU EROSION CONTROL PLAN APPROV BUILDINGS MUST MEET ALL APPL 	RANCE RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. AL REQUIRED.	 16. THIS SITE DOES NOT REQUIRE 17. LANE CLOSURES ON THOROU AND DETAILS, UNLESS OTHER CLOSURES ON HOLIDAYS INCL ACCORDANCE WITH THE NCE CLOSURES AND MUST BE APP
 A PPROVAL OF SITE PLAN DOES NOT CONSTITUTE APPROVAL OF SIGNS. SEPARATE SIGN PERMITS ARE REQUIRED. A 12. CONTRACTOR SHALL NOTIFY PUBLIC WORKS STREET MAINTENANCE DIVISION 48 HOURS PRIOR TO MAKING CONNECTIONS TO EXISTING STORM DRAINS LOCATED WITHIN PUBLIC STORM DRAINAGE EASEMENTS OR R/W. 	A	CODE REQUIREMENTS. 8. NCDOT AND DRIVEWAY PERMITS 9. REFUSE COLLECTION SHALL BE PR 10. ALL DIMENSIONS ARE TO BACK O 11. APPROVAL OF SITE PLAN DOES NO 12. CONTRACTOR SHALL NOTIFY PUBL	ARE REQUIRED. OVIDED BY PRIVATE CONTRACTOR. CURB UNLESS OTHERWISE NOTED. DT CONSTITUTE APPROVAL OF SIGNS. SEPARATE SIGN PERMITS ARE REQUIRED. LIC WORKS STREET MAINTENANCE DIVISION 48 HOURS PRIOR TO MAKING CONNECTIONS TO	 ALL SITE LIGHTING SHALL CO. NEW BUILDINGS MUST COM.

3


4

1

8

11

DEVELOPMENT PLANS FOR COMUNICATIONS HEADQUARTERS INTON, SAMPSON COUNTY, NC



VICINITY MAP 1" = 500'

MUST BE MADE AVAILABLE AT ALL TIMES.

WIDTH AND CENTERED OVER ELECTRIC LINES AS INSTALLED.

S OR OTHER IMPROVEMENTS, MATERIALS AND SURFACES, INCLUDING BUT NOT LIMITED TO STRUCTURES AND ADDITIONS AND APPURTENANCES THERETO, SIGNAGE, FENCES, WALLS, CANOPIES, ANTENNAS, MASTS, DEBRIS, SOLID WASTE COLLECTION CONTAINERS, MAIL OUS SURFACES SHALL ENCROACH WITHIN ANY DEDICATED EASEMENT WITHOUT PRIOR

ANNEXATION UPON APPROVAL OF SITE PLAN.

UGHFARE ROADS ARE ONLY PERMITTED BETWEEN THE HOURS CITY OF CLINTON STANDARD RWISE PERMITTED BY THE TRAFFIC ENGINEER IN ADDITION , THERE WILL BE NO LANE LUDING THE DAY BEFORE OR AFTER SAID HOLIDAY. A TRAFFIC CONTROL PLAN PREPARED IN DOT MANUAL OF UNIFORM TRAFFIC CONTROL DEVISES IS REQUIRED FOR ALL LANE PROVED BY THE TRAFFIC ENGINEER.

DMPLY WITH THE CITY OF CLINTON STANDARD AND DETAILS LIGHTING STANDARD.

IPLY WITH NC FIRE CODE SECTION 510-EMERGENCY RESPONDER RADIO COVERAGE.

	Sh
Sheet Numbe	r
C 0.0	CC
C 0.1	EX PL
C 1.1	SI
C 1.11	SI
C 1.12	SI
C 2.11	UT
C2.12	UT
C 3.11	GF
C3.12	GF
C 4.11	EF
C 4.12	EF
C 5.1	SI
C 5.2	SI
C 5.3	W
C 5.4	SE
C 6.1	EF
C 6.2	EF
C 6.3	EF
L 1.11	LA
L 2.11	LA

CIVIL ENGINEER


Rivers & Associates, Inc. Greenville, NC




107 East Second Street Greenville, NC 27858 (252) 752-4135

Contact: Steve Janowski, PE sjanowski@riversandassociates.com


6	7	8	9	10	11	12







		1	2		3		4	5		6
М										
 L										
						NCGRID (NAD83/2011)				
К										
J										
н										
	-									
G 	-									
F										COMP
 E										еритом + 50% ем. 160 гел 56 ем. 1 голица - не 2000га не
										BENTON & SONS & BE SEA THE SONS & DE SEA THE SONS HE I STATURE THE
223 11:21:42 AM - SAM FLOYD										PJTT - UP
- C 1.1 SITE OVERALL - 7/18/2C O										•••
G\SHEETS\SITE OVERALL.DWG									CONTRACTOR WITH UTILITY C ASSOCIATED F OF THE POWEF UNDERGROUN	
R:\LANDDEV,JKF-STAR_COMM_CLINTON-2023011\CADD_DWG\SHEETS\SITE OVERALL.DWG - C 1.1 SITE OVERALL - 7/18/2023 11:21:42 AM - SAM FLOYD										
R:\LANDDEV\JKF-STAR_COMM_ >				1						
-		1	2		3		4	5		6






7	8	9	10	11	12
I	I	I	I		1








	13	14	15		
				GENERAL NOTES	
				 ALL SITE WORK SHALL BE DONE IN ACCORDANCE WITH THE PLANS PREPARED BY RIVERS AND ASSOCIATES, INC., THE CURRENT REQUIREMENTS OF THE CITY/TOWN OF CLINTON, THE APPLICABLE SECTIONS OF THE NCDOT STANDARD SPECIFICATIONS FOR ROADWAY CONSTRUCTION, AND ALL OTHER PERTINENT FEDERAL, STATE AND LOCAL LAWS. THE CONTRACTOR SHALL COMPLY AT ALL TIMES WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS, PROVISIONS, AND POLICIES GOVERNING SAFETY AND HEALTH, INCLUDING THE FEDERAL CONSTRUCTION SAFETY ACT (PUBLIC LAW 91-54), FEDERAL REGISTER, CHAPTER XVII, PART 1926 OF TITLE 29 REGULATIONS, OCCUPATIONAL SAFETY AND HEALTH REGULATIONS FOR CONSTRUCTION, AND SUBSEQUENT PUBLICATIONS UPDATING THESE REGULATIONS. 	N
				 THE CONTRACTOR SHALL BE RESPONSIBLE FOR EXAMINING THE AREAS AND CONDITIONS UNDER WHICH THE PROJECT IS TO BE CONSTRUCTED PRIOR TO THE SUBMISSION OF A BID. SUBMISSION OF A BID SHALL BE CONSTRUCT O MEAN THE CONTRACTOR HAS REVIEWED THE SITE AND IS FAMILIAR WITH CONDITIONS AND CONSTRAINTS OF THE SITE. BEFORE EXCAVATION, ALL UNDERGROUND UTILITIES SHALL BE LOCATED IN THE FIELD BY THE PROPER AUTHORITIES. THE CONTRACTOR SHALL NOTIFY N.C. ONE CALL AT 1-800-632-4949. THE LOCATION OF ALL UTILITIES AND UNDERGROUND STRUCTURES ARE APPROXIMATE AND MAY NOT ALL BE SHOWN. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE THE EXISTENCE AND EXACT LOCATION OF ALL UTILITIES AND UNDERGROUND STRUCTURES. CONTRACTOR SHALL REFER TO THE GEOTECHNICAL REPORT PRIOR TO INITIATION OF ANY EARTHWORK ACTIVITY. 	L
				 CONTRACTOR IS RESPONSIBLE FOR TRAFFIC CONTROL PLAN - TO BE SUBMITTED TO AND APPROVED BY NCDOT AND THE CITY/TOWN OF CLINTON. CONTRACTOR SHALL NOTIFY PUBLIC WORKS STREET MAINTENANCE DIVISION 48 HOURS PRIOR TO MAKING CONNECTIONS TO EXISTING STORM DRAINS LOCATED WITHIN PUBLIC 	
				 STORM DRAINAGE EASEMENTS OR R/W. 8. REFER TO #### FOR SURVEY CONTROL INFORMATION. 9. CONTRACTOR SHALL REFER TO OTHER PLANS WITHIN THIS CONSTRUCTION SET FOR OTHER PERTINENT INFORMATION. 5. THIS SITE IS NOT LOCATED IN A ZONE 'X' (AREA DETERMINED TO BE OUTSIDE 0.2% ANNUAL CHANCE 100 YEAR FLOODPLAIN) AS IDENTIFIED BY FEMA FLOOD INSURANCE RATE MAP 3720148400K, EFFECTIVE JULY 19, 2022. 6. NO BUILDINGS, STRUCTURES OR OTHER IMPROVEMENTS, MATERIALS AND SURFACES, INCLUDING BUT NOT LIMITED TO PRINCIPLE AND ACCESSORY STRUCTURES AND ADDITIONS AND APPURTENANCES THERETO, SIGNAGE, FENCES, WALLS, MECHANICAL EQUIPMENT, CANOPIES, ANNTENNAS, MASTS, DEBRIS, SOLID WASTE COLLECTION CONTAINERS, MAIL RECEPTACLES, AND IMPERVIOUS SURFACES SHALL NOT ENCROACH WITHIN ANY DEDICATED EASEMENT WITHOUT PRIOR APPROVAL OF CITY/TOWN OF CLINTON PUBLIC UTILITIES DEPARTMENT. 	K
				 SOIL EROSION AND SEDIMENTATION CONTROL PLAN APPROVAL BY NCDENR - LAND QUALITY SECTION REQUIRED PRIOR TO INITIATION OF ANY LAND DISTURBING ACTIVITIES. WETLANDS ARE VALUABLE NATURAL RESOURCES THAT PROVIDE IMPORTANT ECOLOGICAL FUNCTIONS. BE ADVISED THAT ACTIVITIES IN WETLANDS ARE REGULATED BY THE FEDERAL GOVERNMENT UNDER SECTION 404 OF THE CLEAN WATER ACT. JURISDICTIONAL WETLANDS MAY INCLUDE THE PINE-SHRUB POCOSINS THAT ARE COMMON IN THIS REGION. IF ANY PRIVATE LAND OWNER, DEVELOPER, CORPORATION, OR OTHER PERSON PROPOSES TO UNDERTAKE CONSTRUCTION/FILLING ACTIVITIES IN OR NEAR A LAKE, STREAM, CREEK TRIBUTARY OR ANY UNNAMED BODY OF WATER INCLUDING ITS ADJACENT WETLANDS, FEDERAL PERMIT AUTHORIZATION MAY BE REQUIRED FROM THE U.S. ARMY CORPS OF ENGINEERS PRIOR TO COMMENCEMENT OF SUCH LAND-DISTURBING ACTIVITIES. PLEASE CONTACT MS. TRACY WHEELER, TELEPHONE (252) 975-1616 FOR A WETLAND DETERMINATION AND INFORMATION REGARDING SPECIFIC PERMIT REQUIREMENTS. WETLANDS DETERMINATION PENDING, BY OTHERS. APPROVAL OF SITE PLAN DOES NOT CONSTITUTE APPROVAL OF SIGNS. SEPARATE SIGN 	J
				 PERMITS ARE REQUIRED. ALL SLOPES SHALL BE 3:1 (HORIZONTAL:VERTICAL) MAXIMUM UNLESS NOTED OTHERWISE. ALL AREAS NOT PAVED SHALL BE TOPSOILED, SEEDED, MULCHED OR LANDSCAPED/SODDED UNLESS OTHERWISE NOTED IN THE CONSTRUCTION DRAWINGS, SITE SPECIFICATIONS OR INSTRUCTED BY THE OWNER. CONTRACTOR SHALL CONTACT THE FOLLOWING NCDOT OFFICE PRIOR TO BEGINNING WORK WITHIN RIGHT OF WAY (MIN. 5 DAYS NOTICE REQUIRED): SAMPSON COUNTY DISTRICT ENGINEER'S OFFICE (910)682-5100. ALL REQUIRED IMPROVEMENTS SHALL COMPLY WITH THE TOWN OF CLINTON ZONING ORDINANCE REFUSE COLLECTION SHALL BE PROVIDED BY PRIVATE CONTRACTOR. CONTRACTOR IS RESPONSIBLE FOR INSTALLING AND MAINTAINING A CONSTRUCTION ACCESS ROAD A MINIMUM OF 15' WIDE FROM THE EXISTING PAVEMENT TO THE SITE FUNCTION AND MUM MUM OF DETTU OF CLINED 	F
				EXISTING PROPOSED EXISTING PROPERTY LINE ADJ. PROPERTY LINE 	G
					F
				5' WOOD MULCH TRAIL	E
				NO REVISION DATE	
8				SUAL 12324 WEINER HEN JANOUT	С
'GS MONUI		RAI Project #2023011		625 LYNNDALE CT., SUITE F, GREENVILLE, NC 27858 252-355-1068	
GS MONUI ECKER = 452,520 = 2,195,8	0.10' 70.14'		NC License: F-0334 IVELICENSE & ASSOCIATES, INC. tes.com Since 1918	STAR COMMUNICATIONS NEW HEADQUARTERS CITY OF CLINTON- SAMPSON COUNT- NC DRAWING TITLE	В
		riversandassocia Six Forks Place III Ste. 23 353 E. Six Forks Road	0 Engineers Planners	SITE PLAN-SOUTH	
		Raleigh, NC 27609 919.594.1626 EDA INVESTMENT NO. 04-01-074	Surveyors Landscape Architects	SCALE DRAWING NO	
		SCO# 19-20081-01A; NCCCS #	2436	DRAWN MS CHECKED	
		40' SCAL	0 20' 40' E 1 inch = 40 ft	JSJ DATE 07-15-2023 PROJECT NO. 202311	А

COPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA











	1		2			3		4			5	6
										+ ^{152.50}	+1\$2.55	
м											St /	
										/ / + ^{152.52} (
L											2	R
									1	Ç		S DI101
									+153.14	152.98		
											52.92	
К												
	STRUCT		7	PIPE TA]	•			153.21	
	NAME	DETAILS RIM= 152.95'	PIPE NAME	SIZE MATER	IAL LENGTH	SLOPE		\searrow_{G}	RA VEL			
J	CB103	INV= 147.81' (SW) NV= 147.81' (NE-OUT) RIM= 154.45'	P:101-102 P:102-103	18" RCF 18" RCF	161.19				NEW FH 8"X			
		INV= 149.31' (S) INV= 149.31' (SE) NV= 149.27' (NE-OUT) RIM= 154.54'	P:103-104 (1) P:104-105	15" RCF 15" RCF	168.20'	0.60%			H I DRAN	" TEE 6" GV /		
	CB105 CI-BOX 106	INV= 150.32' (N-OUT) RIM= 155.28' INV= 149.65' (S)	P:106-104 P:107-106 P:108-107	8" PVC SCHEE 8" PVC SCHEE 6" PVC SCHEE	OULE 40 62.36	0.60% 0.60% 0.60%				_/153.4 		
		INV = 150.03' (E) NV = 149.65' (NW-OUT) RIM = 155.98' INV = 150.03' (E)	P:109-106	6" PVC SCHEE		0.60%				 + ^{153,6}		<u>152.73 Ті</u>
Н	DI101	INV= 150.03' (N-OUT) RIM= 151.60' INV= 144.80' (S)	_					BENTON & SONS DB 1661, P 68 Di P 370 – MA ZONING: HC	#4, LLC B_1219,			
	DI102	NV= 144.80' (NE-OUT) RIM= 152.30' INV= 147.29' (SW) INV= 147.29' (N-OUT)	PIPE NAME	PIPE TA	1	SLOPE		P 370 – MA ZONING: HC	4P 2		1 N 10	
	FES100	RIM= 145.79' INV= 144.00' (SW)	P:201-202	18" RCP 18" RCP 18" RCP	66.38' 153.92' 26.57'	0.74% 0.75% 0.72%						153.
G		RIM= 156.50' NV= 150.18' (W-OUT) RIM= 156.48' NV= 150.18' (W-OUT)	P:203-204	18" RCP 15" RCP	151.40 ['] 84.24 [']	0.60%		×				
	S-57	RIM= 150.79'		8" PVC SCHEDU 12" PVC SCHEDU	JLE 40 25.39'	1.00% 0.93%		GF	RAVEL			
	STRUCT	URE TABLE	P:209-210	12" PVC SCHEDU 12" PVC SCHEDU 10" PVC SCHEDU	JLE 40 17.65'	3.11% 0.16% 0.28%				 ++ ^{154.12}		
	CB203	DETAILS RIM= 153.42' INV= 147.84' (S)	P:214-213 P_204-205	8" PVC SCHEDU 15" RCP	JLE 40 5.62' 87.96'	11.89% 0.60%						
F	IN	RIM= 152.55' RIM= 152.55' IV= 149.81' (N-OUT)	-					8"Xi	8" TEE WITH 2	- 8" GV - /		
		RIM= 152.30' INV= 146.49' (S) /= 146.49' (NW-OUT)	_					_		154 15-		
	DI202	RIM= 152.30' INV= 147.65' (SE) IV= 147.65' (N-OUT)										
E	DI204	RIM= 153.00' INV= 148.75' (S) INV= 148.75' (W) IV= 148.75' (N-OUT)							NEW FH 8"X6" HYDRANT 1	LOCKED		- <u>155.20 T</u> 754
	DI205	RIM= 153.00' INV= 149.28' (S) INV= 149.28' (W) IV= 149.28' (N-OUT)							X3" TEE WITH VC WATER SER	+ +	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 	7:106:10:37
		RIM= 147.79' INV= 146.00' (SE) RIM= 156.50'	_					BENTON & SONS DB 1661, P 68 P 370 – N ZONING: H	5 #4, LLC DB 1219, 14P	E COBO PLAN	3"W	CI/BOX 106-
		IV= 150.61' (E-OUT) RIM= 156.50' IV= 151.27' (S-OUT)	_					ZONING: "F	ΗC			15.80 TC
D	RD212 IN	RIM= 156.50' IV= 150.53' (S-OUT) RIM= 154.97'	_								3" W	
	11208	INV= 149.52' (SW) INV= 150.50' (N) IV= 149.51' (E-OUT) RIM= 154.77'								LOD 8" W		
	IN	INV= 150.30' (W) V= 150.31' (NE-OUT) RIM= 156.16'	-								<u>. 17 TC</u>	<u>155.58 TC</u>
С		INV= 150.60' (N) IV= 150.60' (E-OUT)						PAVEMENT		4.87 4.86	>	CI-BOX 107
										GO 54.44		
							3" WA	ER METER IN VAULT 3" R	PZ−∖	LOD 3" W		
							EL	DA WITH FDC, HEATER, 12 ECTRICAL SERVICE TAMI	PER $\setminus \setminus $	Lob 4		
B							SWI	CH TIED TO ALARM SYS NEW FH 8"X6" LOCH HYDRANT TEE 6"	KED –		<u>55.60 TC</u> _/	
		()										1 <u>35 TC</u> <u>155.7(</u>
			®					EX.STC 12"X8" TAPPING TEE	154.19 154.19 154.19 154.19			
A		CALL BEFOR	E YOU DIG!				R/W	12"X8" TAPPING TEE & GATE VALVE	54. 54. 154.18 154.18 154.18 154.25 154.25 154.25 154.25 154.25 154.25 154.25 154.25 154.25 155 155 155 155 155 155 155 155 155 1		мн	VE AND REPLACE EX CONE AND ADJ RING
/ \		WWW.NC8 N.C. ONE-CAI IT'S THE	311 ORG						155.54 (155.54 (155.18 155.18 (. <u>18" RCP</u>	155.33 155.33	<u></u>	
										x		
	1		2			3		4			5	6




	13	14	15		
·	MATCH LINE			GENERAL NOTES	
					м
					L
					K
WOODED					J
WOODED-	x				
					Η
TON A. DAVIS	5			EXISTING PROPOSED PROPERTY LINE PROPERTY LINE PROPERTY LINE PROPERTY LINE RIGHT OF WAY PROPERTY LINE	
TON A. DAVIS 1650, P 900 B 5, P 67 DNING: HC				— — — 160— MAJOR TOPO — — — MINOR TOPO 159	G
				TOP OF DITCH REINF. CONC. PIPE GRADE BREAK	
				SLOPE ARROW -1.1% × ^{155.86} SPOT ELEVATION EOP 162.80 ASPHALT	
				FUTURE ROAD	
					F
					_
					E
					-
				NO REVISION DATE	D
				SAL J L L	
				ARCHITECTURE	С
				625 LYNNDALE CT., SUITE F, GREENVILLE, NC 27858 252-355-1068	
		RAI Project #2023011			
				STAR COMMUNICATIONS NEW HEADQUARTERS	
		A R	& ASSOCIATES, INC. tes.com Since 1918	CITY OF CLINTON- SAMPSON COUNT- NC	В
		<u>riversandassocia</u> Six Forks Place III Ste. 23 353 E. Six Forks Road	tes.com Since 1918	GRADING AND STORM DRAINAGE PLAN-SOUTH	
		853 E. SIX FORS Road Raleigh, NC 27609 919.594.1626	Surveyors Landscape Architects	SCALE AS SHOWN	
		EDA INVESTMENT NO. 04-01-07 SCO# 19-20081-01A; NCCCS #		DRAWN MS	
-EX.STCB2		30'	0 15' 30'	CHECKED JSJ C 3.11	A
<u>~</u>		SCAI	E 1 inch = 30 ft	07-15-2023 PROJECT NO.	
EX. 15" RCP				© COPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA	
	13	14	15		



	14	15		
			GENERAL NOTES	
				М
				L
				L
				K
				I
				J
				Н
			EXISTING PROPOSED PROPERTY LINE PROPERTY LINE	
				G
			DITCH CENTERLINE TOP OF DITCH REINF. CONC. PIPE	
			GRADE BREAK	
			ASPHALT	
				F
				E
			NO REVISION DATE	D
			SEAL	
			JK H	
			S AVCINE S	
			HEN JANNING ARCHITECTURE	С
F	RAI Project #2023011		625 LYNNDALE CT., SUITE F, GREENVILLE, NC 27858 252-355-1068	
		NC License: F-0334	STAR COMMUNICATIONS NEW HEADQUARTERS	
	{ } K	ASSOCIATES, INC.	CITY OF CLINTON- SAMPSON COUNT- NC	r
	riversandassocia Six Forks Place III Ste. 23	tes.com Since 1918	GRADING AND STORM	В
	313 Forks Flace III Ste. 23 353 E. Six Forks Road Raleigh, NC 27609 919.594.1626	Planners Surveyors Landscape Architects	DRAINAGE PLAN-NORTH	
E	919.594.1626 Da investment no. 04-01-07 Co# 19-20081-01a; ncccs #	418	AS SHOWN	
3	CO# 19-20081-01A; NCCCS #	0 20' 40'		A
			JSJ C3.12 DATE 07-15-2023	/ \
	SCAL	_E 1 inch = 40 ft	PROJECT NO. 202311	
	14	15	COPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA	

13



TOTAL DISTURBED AREA = 6.00 ACRES

SPILLWAY. CHECK THE EMBANKMENT, SPILLWAYS, AND OUTLET FOR EROSION DAMAGE, AND INSPECT THE EMBANKMENT FOR PIPING AND SETTLEMENT. MAKE ALL NECESSARY REPAIRS IMMEDIATELY. REMOVE ALL TRASH AND OTHER DEBRIS FROM THE SKIMMER AND POOL AREAS. FREEZING WEATHER CAN RESULT IN ICE FORMING IN THE BASIN. SOME SPECIAL PRECAUTIONS SHOULD BE TAKEN IN THE WINTER TO PREVENT THE

IF THE SKIMMER ARM OR BARREL PIPE IS CLOGGED, THE ORIFICE CAN BE REMOVED AND THE OBSTRUCTION CLEARED WITH A PLUMBER'S SNAKE OR BY FLUSHING WITH WATER. BE SURE AND REPLACE THE ORIFICE BEFORE REPOSITIONING THE SKIMMER.

IF THE SKIMMER IS CLOGGED WITH TRASH AND THERE IS WATER IN THE BASIN, USUALLY JERKING ON THE ROPE WILL MAKE THE SKIMMER BOB UP AND DOWN AND DISLODGE THE DEBRIS AND RESTORE FLOW. IF THIS DOES NOT WORK, PULL THE SKIMMER OVER TO THE SIDE OF THE BASIN AND

THE BASIN DOES NOT HOLD DOWN THE SKIMMER. REPAIR THE BAFFLES IF THEY ARE DAMAGED. RE-ANCHOR THE BAFFLES IF WATER IS FLOWING UNDERNEATH OR AROUND THEM.

MAINTENANCE INSPECT SKIMMER SEDIMENT BASINS AT LEAST WEEKLY AND AFTER FACH SIGNIFICANT (ONE-HALE INCH OR GREATER) RAINFALL EVENT AND REPAIR IMMEDIATELY. REMOVE SEDIMENT AND RESTORE THE BASIN TO ITS ORIGINAL DIMENSIONS WHEN SEDIMENT ACCUMULATES TO ONE-HALF THE HEIGHT OF THE FIRST BAFFLE PULL THE SKIMMER TO ONE SIDE SO THAT THE SEDIMENT UNDERNEATH IT CAN BE EXCAVATED. EXCAVATE THE SEDIMENT FROM THE ENTIRE BASIN, NOT JUST AROUND THE SKIMMER OF THE FIRST CELL. MAKE SURE VEGETATION GROWING IN THE BOTTOM OF

10) INSTALL POROUS BAFFLES. 11) AFTER ALL THE SEDIMENT-PRODUCING AREAS HAVE BEEN PERMANENTLY STABILIZED, REMOVE THE STRUCTURE AND ALL THE UNSTABLE SEDIMENT. SMOOTH THE AREA TO BLEND WITH THE ADJOINING AREAS AND STABILIZE PROPERLY.

INSUFFICIENT FOR THE ENTIRE LENGTH OF THE SPILLWAY. MULTIPLE SECTIONS. SPANNING THE COMPLETE WIDTH. MAY BE USED. THE UPPER SECTION(S) SHOULD OVERLAP THE LOWER SECTION(S) SO THAT WATER CANNOT FLOW UNDER THE FABRIC. SECURE THE UPPER EDGE AND SIDES OF THE FABRIC IN A TRENCH WITH STAPLES OR PINS. 8) INLETS - DISCHARGE WATER INTO THE BASIN IN A MANNER TO PREVENT EROSION. USE TEMPORARY SLOPE DRAINS OR DIVERSIONS WITH OUTLET PROTECTION TO DIVERT SEDIMENT-LADEN WATER TO THE UPPER END OF THE POOL AREA TO IMPROVE BASIN TRAP EFFICIENCY 9) FROSION CONTROL - CONSTRUCT THE STRUCTURE SO THAT THE DISTURBED AREA IS MINIMIZED. DIVERT SURFACE WATER AWAY FROM BARE AREAS. COMPLETE THE EMBANKMENT BEFORE THE AREA IS CLEARED. STABILIZE THE EMERGENCY SPILLWAY EMBANKMENT AND ALL OTHER


5) ASSEMBLE THE SKIMMER FOLLOWING THE MANUFACTURERS INSTRUCTIONS, OR AS DESIGNED. 6) LAY THE ASSEMBLED SKIMMER ON THE BOTTOM OF THE BASIN WITH THE FLEXIBLE JOINT AT THE INLET OF THE BARREL PIPE ATTACH THE FLEXIBLE JOINT TO THE BARREL PIPE AND POSITION THE SKIMMER OVER THE EXCAVATED PIT OR SUPPORT. BE SURE TO ATTACH A ROPE TO THE SKIMMER AND ANCHOR IT TO THE SIDE OF THE BASIN THIS WILL BE USED TO PLUL THE SKIMMER TOTHE SIDE FOR MAINTENANCE 7) EARTHEN SPILLWAYS - INSTALL THE SPILLWAY IN UNDISTURBED SOIL TO THE GREATEST EXTENT POSSIBLE. THE ACHIEVEMENT OF PLANNED ELEVATIONS, GRADE, DESIGN WIDTH, AND ENTRANCE AND EXIT CHANNEL SLOPES ARE CRITICAL TO THE SUCCESSFUL OPERATION OF THE SPILLWAY. THE SPILLWAY SHOULD BE LINED WITH LAMINATED PLASTIC OR IMPERMEABLE GEOTEXTILE FABRIC. THE FABRIC MUST BE WIDE AND LONG ENOUGH TO COVER THE BOTTOM AND SIDES AND EXTEND ONTO THE TOP OF THE DAM FOR ANCHORING IN A TRENCH. THE EDGES MAY BE SECURED WITH 8-INCH STAPLES OR PINS. THE FABRIC MUST BE LONG ENOUGH TO EXTEND DOWN THE SLOPE AND EXIT ONTO STABLE GROUND. THE WIDTH OF THE FABRIC MUST BE ONE PIECE, NOT JOINED OR SPLICED; OTHERWISE WATER CAN GET UNDER THE FABRIC. IF THE LENGTH OF THE FABRIC IS

PLACE A MINIMUM DEPTH OF 2 FEET OF COMPACTED BACKFILL OVER THE PIPE SPILLWAY BEFORE CROSSING IT WITH CONSTRUCTION EQUIPMENT. IN NO CASE SHOULD THE PIPE CONDUIT BE INSTALLED BY CUTTING A TRENCH THROUGH THE DAM AFTER THE EMBANKMENT IS COMPLETE.

MATERIAL. PLACE THE FILL IN LIFTS NOT TO EXCEED 9 INCHES, AND MACHINE COMPACT IT. OVER FILL THE EMBANKMENT 6 INCHES TO ALLOW FOR SETTLEMENT 3) SHAPE THE BASIN TO THE SPECIFIED DIMENSIONS. PREVENT THE SKIMMING DEVICE FROM SETTLING INTO THE MUD BY EXCAVATING A SHALLOW PIT UNDER THE SKIMMER OF PROVIDING A LOW SUPPORT UNDER THE SKIMMER OF STONE OR TIMBER. 4) PLACE THE BARREL (TYPICALLY 4-INCH SCHEDULE 40 PVC PIPE) ON A FIRM, SMOOTH FOUNDATION OF IMPERVIOUS SOIL. DO NOT USE PERVIOUS MATERIAL SUCH AS SAND. GRAVEL, OR CRUSHED STONE AS BACKEILL AROUND THE PIPE. PLACE THE FILL NAL AKOUND THE PIPE SPILLWAY I 4-INCH LAYERS AND COMPACT IT UNDER AND AROUND THE PIPE TO AT LEAST THE SAME DENSITY\ AS THE ADJACENT EMBANKMENT. CARE MUST


CONSTRUCTION SPECIFICATION) CLEAR, GRUB AND STRIP THE AREA UNDER THE EMBANKMENT OF ALL VEGETATION AND ROOT MAT. REMOVE ALL SURFACE SOILCONTAINING HIGH AMOUNTS OF ORGANIC MATTER AND STOCKPILE OR DISPOSE OF IT PROPERLY. HAUL ALL OBJECTIONABLE MATERIAL TO THE DESIGNATED DISPOSAL AREA. PLACE TEMPORARY SEDIMENT CONTROL MEASURES BELOW BASIN AS NEEDED. 2) ENSURE THAT FILL MATERIAL FOR THE EMBANKMENT IS FREE OF ROOTS, WOODY VEGETATION, ORGANIC MATTER, AND OTHEROBJECTIONABLE


SKIMMER BASIN




N.C. ONE-CALL CENTER IT'S THE LAW!


202311 OPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA






202311 OPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA





6	7	8	9	10	11	12



6	7	8	9	10	11	





Table 6.4	0a Seeding mixture	Тото	orary Skimmer Bas	in No. 1
Table 6.1 Temporary Seedi	ng Species Rate (lb/acre)	Тетро	Phase 1 AND 2	
Recommendations for La Winter and Early Spri	1190 (grain)	STAR COMMUN	ICATIONS NEW H	EADQUARTERS
	Piedmont and Coastal Plain, Korean in Mountains) 50		CLINTON, NC	
		Discharge Calculation		SKIMMER
	Omit annual lespedeza when duration of temporary cover is not to extend beyond June.	4.40 Disturbed Area (Acres)		4 Skimmer Size (inches)
	Seeding dates	0.75 Rational C 11 Time of Concentration (min)		0.333 Head on Skimmer (ft) 2 Orifice Size (1/4 inch increments)
	Mountains—Above 2500 feet: Feb. 15 - May 15 Below 2500 feet: Feb. 1- May 1	5.58 Intensity (in/hr) Atlas 14		1.79 Dewatering Time (days)
	Piedmont—Jan. 1 - May 1	18.41 Peak Flow from 10-year Storm ((cfs)	Suggest about 3 days
	Coastal Plain—Dec. 1 - Apr. 15	Dimension Calculation		Skimmer Size
	Soil amendments Follow recommendations of soil tests or apply 2,000 lb/acre ground	7,920 Required Volume (ft^3) = 1800 x I		(inches)
	agricultural limestone and 750 lb/acre 10-10-10 fertilizer.	5,985 Required Surface Area (ft ²) = 32 54.7 Suggested Width (ft)	25 * Q(cfs)	2
	Mulch Apply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting,	109.4 Suggested Length (ft)		2.5
	or a mulch anchoring tool. A disk with blades set nearly straight can be	55 Trial Top Width at Spillway Inver		3
	used as a mulch anchoring tool.	110 Trial Top Length at Spillway Inve 3 Trial Side Slope Ratio Z:1		
	Maintenance Refertilize if growth is not fully adequate. Reseed, refertilize and mulch	2.75 Trial Depth (ft)		
	immediately following erosion or other damage.	12 Bottom Width (ft) 93.5 Bottom Length (ft)		
		1,122 Bottom Area (ft ²)		
	Seeding mixture	9,536 Actual Volume (ft ³)	Okay	
Temporary Seeding Recommendations for	SpeciesRate (lb/acre)German millet40	6,050 Actual Surface Area (ft ²)	Okay	
Summer		Spillway Calculation		
	In the Piedmont and Mountains, a small-stemmed Sudangrass may be substituted at a rate of 50 lb/acre.	18 Trial Weir Length (ft)		
	Seeding dates	0.5 Trial Depth of Flow (ft) 19.1 Spillway Capacity (cfs)	Okay	
	Mountains—May 15 - Aug. 15	0.49 Actual Depth (ft)		
	Piedmont—May 1 - Aug. 15 Coastal Plain—Apr. 15 - Aug. 15	2.10 Velocity (cfs)		
	Soil amendments	145.50 Spillway Top Elev (ft) 145.99 10-yr WSEL (ft)		
	Follow recommendations of soil tests or apply 2,000 lb/acre ground	147.00 Basin Top		
	agricultural limestone and 750 lb/acre 10-10-10 fertilizer.	1.00 Freeboard	Okay	
	Maintenance Refertilize if growth is not fully adequate. Reseed, refertilize and mulch immediately following erosion or other damage.	JOB STA SHEET NO. CALCULATE	ED BY MS DATE 5/12	2/2023
Table 6.10 Temporary Seeding ecommendations for Fal		CHECKED E SCALE		2/2023
	Seeding dates Mountains—Aug. 15 - Dec. 15 Coastal Plain and Piedmont—Aug. 15 - Dec. 30	Outlet pipe diameter (Do) $W = D_0 + L_a$	90,	Outlet $W = D_0 + L_a$ diameter (D ₀)
	Soil amendments Follow soil tests or apply 2,000 lb/acre ground agricultural limestone and 1,000 lb/acre 10-10-10 fertilizer.	Tailwater < 0.500 Inum Length of Apron (La)(11). 70		Tailwater < 0.5Do
	Mulch Apply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting, or a mulch anchoring tool. A disk with blades set nearly straight can be used as a mulch anchoring tool.			
	Maintenance Repair and refertilize demograd areas immediately. Tendross with 50	10	13	
	Repair and refertilize damaged areas immediately. Topdress with 50 lb/acre of nitrogen in March. If it is necessary to extent temporary	0	277777	
	cover beyond June 15, overseed with 50 lb/acre Kobe (Piedmont and Coastal Plain) or Korean (Mountains) lespedeza in late February or	V = 25.		0 Ripre
	early March.	v = 15		$v = \frac{15}{2}$
		<u>v = 5</u>		v = 10° 0
		3 5 10 20 50 Discharge (ft ³ /	100 200 500 (sec)	1000 3 5 10 20 D
		Given Information	Calculated Information	Given Information
		Q ₁₀ = 7.60 cfs Width at entrance	$\begin{array}{c} \text{Calculated monitormation} \\ \text{Calculated monitormation} \\$	$Q_{10} = 7.40 \text{ cfs}$ $D_0 = 18 \text{ "}$
			from chart) L = <u>8</u> ft 22 " thick Class 'B' stone	Class 'B' stone unit weight = 110 pcf L Is flow below minimum for Pipe Diameter. YES
				and the second
		If flow is higher, then chart consultation is needed Tonnage = 4.0	033333 tons use <u>5 tons</u>	Apron at FES #200
				Apron at FES #200 Use 5 ft x 5 ft x 8 ft,5 tons.
		If flow is higher, then chart consultation is needed Tonnage 4.0 Apron at FES #100 Apron at FES #100 Apron at FES #100		Apron at FES #200
		If flow is higher, then chart consultation is needed Tonnage 4.0 Apron at FES #100 Apron at FES #100 Apron at FES #100		Apron at FES #200
		If flow is higher, then chart consultation is needed Tonnage 4.0 Apron at FES #100 Apron at FES #100 Apron at FES #100		Apron at FES #200
		If flow is higher, then chart consultation is needed Tonnage 4.0 Apron at FES #100 Apron at FES #100 Apron at FES #100		Apron at FES #200
		If flow is higher, then chart consultation is needed Tonnage 4.0 Apron at FES #100 Apron at FES #100 Apron at FES #100		Apron at FES #200
		If flow is higher, then chart consultation is needed Tonnage 4.0 Apron at FES #100 Apron at FES #100 Apron at FES #100		Apron at FES #200

6	7		8	9	
		i.			
-	Temporary Sk	imn	ner Basin No. 1		
	Phas	<u>e 1</u> /	AND 2		
STAR CO	MMUNICATIC	NS	NEW HEADQUA	ARTERS	
	CLI	NTON	N, NC		
harge Calcula:	tion			SKIMMER	
ed Area (Acres	3)		4 :	Skimmer Size (inches)	
al C			0.333	Head on Skimmer (ft)	
f Concentration	(min)		2	Orifice Size (1/4 inch incremer	nts)
y (in/hr) Atlas 1	4		1.79	Dewatering Time (days)	
low from 10-ye	ar Storm (cfs)			Suggest about 3 days	
		_			
ension Calcula				Skimmer Size	
ed Volume (ft ³)	-	_		(inches)	
ed Surface Area	a (ft ²) = 325 * Q(cfs)			1	
sted Width (ft)				2	
sted Length (ft)				2.5	
op Width at Spil	· · ·			3	
	illway Invert (ft)				
de Slope Ratio	Z:1				
epth (ft)					
Width (ft)		_			
Length (ft)					
Area (ft ²)					
Volume (ft ³) Surface Area (f	+ ² \	Okay			
Sullace Alea (I	()	Okay	y and a second s		
llway Calculat	ion				
/eir Length (ft)					
epth of Flow (ft))				
y Capacity (cfs		Okay	y		
Depth (ft)					
y (cfs)					
y Top Elev (ft)					
VSEL (ft)					
⁻ ор					
ard		Okay	у		
					-

11	12	13	14	15		
					GENERAL NOTES	
	IONS for Temporary S					
SUNSET A	AVE. CLINTON , NC					М
Swale 1 in to Outlet Based on 10 year storm	emporary condition	n				
Total watershed area (Ac) 3.2						
Land Type F Area Impervious denuded with temporary seeding	Rational C CN Acres 0.95 98 0.33 73	<u>0.000</u> 2.360				
Total watershed area	0.33	2.360				L
OverlandHydraulic Length (ft)1,067Vertical Relief (ft)9.00	Channelized 1,070 9.50					
Time of Concentration	9.50					
$I_{t} = \begin{bmatrix} \overline{H} \end{bmatrix}$ Time (min) 21.08		<10, use 10 min				
'c $\overline{128}$ Travel Factor2Rainfall Intensity =I = g/(h+T)Peak Discharge =Q=CIA	0.2 4.9 inches per hr 3.8 cfs	g 225 h 22.5				
Right Side SlopeLeft Side Slope2.002.00		Innel VeloctiyFlow Depth3.94 fps0.70 ft				К
Tractive ForceTd= YDS (lb/sf)0.387	use temporary liner Curled wood mat Td=	1.55 lb/sf ok				
	IONS for Temporary S		_			
	TIONS NEW HEADQU AVE. CLINTON , NC	ARTERS	_			J
	temporary conditio	n				
Outlet Based on 10 year storm Total watershed area (Ac) 1.47						
Land Type F Area Impervious	Rational C CN Acres	0.000				
denuded with temporary seeding Total watershed area	0.35 73	1.470 1.470				Н
CompositeOverlandHydraulic Length (ft)561	Channelized 561					
Vertical Relief (ft) 9.00	9.00					
\overline{H} Time (min) 10.03	Channelized Total 1.00 11.04 If Tc•	<10, use 10 min				
Image: 128 Travel Factor 2 Rainfall Intensity = I = g/(h+T)	0.2 6.7 inches per hr	g 225				
Peak Discharge =Q=CIARight Side SlopeLeft Side Slope2.002.00	3.5 cfs n= Slope Cha 0.022 1.60%	h 22.5 annel Veloctiy Flow Depth 2.47 fps 0.84 ft				G
Tractive Force	use temporary liner					
Td= YDS (lb/sf) 0.836	jute netting = Td=	0.45 lb/sf ok				
COMMUNICATIONS NEW HEADQUARTERS						
2 OF 2 BY MS DATE 5/12/2023 JSJ DATE 5/12/2023	_					F
	EROS	ION CONTROL NO	TES AND CACULATIO	NS:		
90,						
80	LEC	GEND:				E
		X	DEMO ITEM			
		~ ~				
4	_		SILT FENCE LIMITS OF DISTURBANCE			
1-3-10			CLEARING LIMITS			
		$\nabla \ \nabla$	SILT FENCE OUTLET (SFO)		NO REVISION DATE	D
2 Sig			TEMPORARY STANDARD HAR CLOTH AND GRAVEL INLET P		SEAL	
1 gg		****	ROCK DAM			
			OUTLET STRUCTURE			
100 200 500 1000	_		SKIMMER		ARCHITECTURE	С
Calculated Information			Al Project #2023011		625 LYNNDALE CT., SUITE F, GREENVILLE, NC 27858 252-355-1068	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$						
" thick Class 'B' stone 3333 tons use 5 tons				NC License: F-0334	STAR COMMUNICATIONS NEW HEADQUARTERS	
			Riv		CITY OF CLINTON- SAMPSON COUNT- NC DRAWING TITLE	В
		r	iversandassociates.c Six Forks Place III Ste. 230	Engineers	EROSION CONTROL NOTES	
		G F	853 E. Six Forks Road Raleigh, NC 27609	Planners Surveyors		
		EC	DA INVESTMENT NO. 04-01-07418	ndscape Architects	SCALE DRAWING NO	
		SC	CO# 19-20081-01A; NCCCS #2436		CHECKED	
					JSJ C. 6 1	A
					PROJECT NO.	
11	12	13	14	15	© COPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA	
I I						


Seeding mixture SpeciesRate (Ib/acre)Rye (grain)120Annual lespedeza (Kobe in Piedmont and Coastal Plain, Korean in Mountains)50	Temporary Skimmer Basin No Phase 1 AND 2 STAR COMMUNICATIONS NEW HEADO	o. 1	SWALE CALCULATIONS for T STAR COMMUNICATIONS NEV	W HEADQUARTERS			
Rye (grain) 120 Annual lespedeza (Kobe in Piedmont and Coastal Plain,							
Annual lespedeza (Kobe in Piedmont and Coastal Plain,	STAR COMMUNICATIONS NEW HEAD		SUNSET AVE. CLIN	TON NC			
*		QUARTERS					M
	CLINTON, NC		Swale 1 in temporar Outlet Based on 10 year storm	y condition			
	Discharge Calculation	SKIMMER	Total watershed area (Ac) 3.2				
Omit annual lespedeza when duration of temporary cover is not to extend beyond June.	4.40 Disturbed Area (Acres)	4 Skimmer Size (inches)	Land TypeRational CArea Impervious0.95				
Seeding dates		.333 Head on Skimmer (ft)	denuded with temporary seeding 0.33 Total watershed area	3 73 <u>2.360</u> 2.360			
Mountains—Above 2500 feet: Feb. 15 - May 15	11 Time of Concentration (min) 5.58 Intensity (in/hr) Atlas 14	2 Orifice Size (1/4 inch increments) 1.79 Dewatering Time (days)	Composite 0.33 Overland Channelized		_		L
Below 2500 feet: Feb. 1- May 1 Piedmont—Jan. 1 - May 1	18.41 Peak Flow from 10-year Storm (cfs)	Suggest about 3 days	Hydraulic Length (ft) 1,067 1,070				
Coastal Plain—Dec. 1 - Apr. 15							
Soil amendments			$\begin{bmatrix} L^3 \end{bmatrix}^{0.385}$ Overland Channelized				
	5,985 Required Surface Area (ft^2) = 325 * Q(cfs)	1	$l_c = \frac{1}{128}$ Travel Factor 2 0.2				
	54.7 Suggested Width (ft)	2	Peak Discharge = Q=ČIA 3.8	cfs h 2	.5		
Apply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting,		2.5	Right Side SlopeLeft Side Slopen=2.002.000.022	SlopeChannel VeloctiyFlow Dept0.89%3.94 fps0.70 ft			K
		5	Tractive Force use tempora				
	3 Trial Side Slope Ratio Z:1		Td= YDS (lb/sf) 0.387 Curled wood	od mat Td= 1.55 lb/sf ok			
Refertilize if growth is not fully adequate. Reseed, refertilize and mulch	2.75 Trial Depth (ft)						
immediately following erosion or other damage.							
	1,122 Bottom Area (ft ²)						
eeding mixture	9,536 Actual Volume (ft ³) Okay						
Species Rate (Ib/acre) German millet 40	6,050 Actual Surface Area (tt ⁻) Okay		Swale 2 in temporal Outlet Based on 10 year storm	y condition			
	Spillway Calculation		Total watershed area (Ac) 1.47	· · · · · · · · · · · · · · · · · · ·			\vdash
the Piedmont and Mountains, a small-stemmed Sudangrass may be	18 Trial Weir Length (ft)		Area Impervious 0.95	<u>5 98 0.000</u>			
	0.5 Trial Depth of Flow (ft) 19.1 Spillway Capacity (cfs)			5 73 1.470 1.470			
-			Composite 0.35 Overland Channelized		-		н
edmont—May 1 - Aug. 15	2.10 Velocity (cfs)		Hydraulic Length (ft) 561 561				
	147.00 Basin Top		$\begin{bmatrix} L^3 \end{bmatrix}^{0.385}$ Overland Channelized				
pricultural limestone and 750 lb/acre 10-10-10 fertilizer.	1.00 Freeboard Okay		$I_c = \frac{1}{128}$ Travel Factor 2 0.2	2	25		
ulch			Peak Discharge = Q=CIA 3.5	o cfs h 2	2.5 b		G
oply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting,			2.00 2.00 0.022	Slope Channel Velocity Flow Dep 2 1.60% 2.47 fps 0.84 ft	<u></u>		
a mulch anchoring tool. A disk with blades set hearly straight can be							
aintenance				ng = 1a= 0.45 lb/st ok			
efertilize if growth is not fully adequate. Reseed, refertilize and mulch							
mediately following erosion or other damage.	SHEET NO. 1 OF 2		JOB STAR COMMUNICATIONS NEW HEADQUARTERS SHEET NO. 2				
	CALCULATED BY MS DATE 5/12/2023 CHECKED BY JSJ DATE 5/12/2023		CHECKED BY JSJ DATE 5/12/2023				F
•				EROSION CONTROL I	IOTES AND CACULATIONS:		
Rye (grain) 120							
Seeding dates	3D0	3D0					
Mountains—Aug. 15 - Dec. 15	Outlet $W = D_0 + L_a$ 90	Outlet $W = D_0 + L_a$	90, 1111				
	diameter (Do) $L_a \rightarrow 0.5D_a$	diameter (Do) \Box	80	LEGEND:			E
Soil amendments Follow soil tests or apply 2 000 lb/acre ground agricultural limestone	on (La)(P). 70		(¹¹⁾ . 70,	×			
and 1,000 lb/acre 10-10-10 fertilizer.	Length of API 60	Length of Api 60					
Mulch	Minimum 50	Minimum 50		SF	SILT FENCE		
Apply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting,					LIMITS OF DISTURBANCE		
used as a mulch anchoring tool.		30,1			CLEARING LIMITS		
Maintenance				$\nabla \nabla \nabla$	SILT FENCE OUTLET (SFO)	NO REVISION DATE	D
Repair and refertilize damaged areas immediately. Topdress with 50		Size (1			TEMPORARY STANDARD HARDWARE	SEAL	
cover beyond June 15, overseed with 50 lb/acre Kobe (Piedmont and	V= 25 mm to 10 mm to	liprap	25		CLOTH AND GRAVEL INLET PROTECTION	TH CARO	
	$\frac{1}{1}$	1 090 5	1 ¹⁰ Sp	3335	ROCK DAM	SEA FINE	
	$v = 15$ 2^{-12}	v = 15 $v = 10$ 0			OUTLET STRUCTURE		▶ ■
	3 5 10 20 50 100 200 500 1000	3 5 10 20	50 100 200 500 1000		SKIMMER	ARCHITEC	CTURE c
	Discharge (ft ³ /sec)	Disc	harge (ft ³ /sec)				
	Given Information Calculated Information Q_{10} = 7.60 cfs Width at entrance = 3D ₀ = 4.5 ft use 5.0 ft	Given Information	Calculated Information th at entrance = $3D_0$ = 4.5 ft use 5.0 ft		RAI Project #2023011	625 LYNNDALE CT., SUITE F, GREENVILLE, NC 27858 2	52-355-1068
	D_o =18"Width at exit (D_o + 0.4xL _a)=4.7ftuse5.0ftClass 'B' stone unit weight=110pcfLength of Apron (from chart)L =8ft	D ₀ = 18 " Widt	th at exit $(D_0 + 0.4xL_a) = 4.7$ ft use 5.0 ft				NS –
	Is flow below minimum for Pipe Diameter: YES Thickness = 22 " thick Class 'B' stone If flow is higher, then chart consultation is needed Tonnage = 4.033333 tons use 5 tons	Is flow below minimum for Pipe Diameter. YES Thick	kness = 22 " thick Class 'B' stone				
	Apron at FES #100	Apron at FES #200				CITY OF CLINTON- SAMPSON COUNT	- NC
	Use o π x o π x o π, o tons.	Use 5 ft x 5 ft x 8 ft,5 tons.			& ASSOCIATES, INC. riversandassociates.com Since 1918		רבפ ₪
					Six Forks Place III Ste. 230 Engineers		
					Raleigh, NC 27609 Surveyors		ر
						AS SHOWN	
						DRAWN	
							1
						PROJECT NO.	
		I	1			© COPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA	
	Coastal Plain—Dec. 1 - Apr. 15 Soil amendments Follow recommendations of soil tests or apply 2,000 lb/acre ground agricultural limestone and 750 lb/acre 10-10-10 fertilizer. Much Apply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting, or a mulch anchoring tool. A disk with blades set nearly straight can be used as a mulch anchoring tool. Maintenance Refertilize if growth is not fully adequate. Reseed, refertilize and mulch immediately following erosion or other damage. redding mixture Species Rate (lb/acre) German millet 40 the Piedmont and Mountains, a small-stemmed Sudangrass may be betituted at a rate of 50 lb/acre. eding dates puntains—May 15 - Aug. 15 admont—May 1 - Aug. 15 astal Plain—Apr. 15 - Aug. 15 di amendments llow recommendations of soil tests or apply 2,000 lb/acre ground ricultural limestone and 750 lb/acre 10-10-10 fertilizer. Ilch ply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting, a mulch anchoring tool. A disk with blades set nearly straight can be ad as a mulch anchoring tool. A disk with blades set nearly straight can be ad as a mulch anchoring tool. Mintenance fertilize if growth is not fully adequate. Reseed, refertilize and mulch mediately following erosion or other damage. Feeding dates lountains—Aug. 15 - Dec. 15 coestal Plain and Piedmont—Aug. 15 - Dec. 30 Oil amendments Iolow soil tests or apply 2,000 lb/acre ground agricultural limestone nd 1,000 lb/acre straw. Anchor straw by tacking with asphalt, netting, ra mulch anchoring tool. A disk with blades set nearly straight can be and as a mulch anchoring tool. Di amendments Iolow soil tests or apply 2,000 lb/acre ground agricultural limestone nd 1,000 lb/acre 10-10-10 fertilizer. Much pply 4,000 lb/acre straw. Anchor straw by tacking with asphalt, netting, ra mulch anchoring tool. A disk with blades set nearly straight can be sed as a mulch anchoring tool. A disk with blades set nearly straight can be sead as a mulch anchoring tool. Bintenance	Costail Plantbox 1 - Apr. 13 Solid Plantbox 2 - Apr. 14 Solid Plantbox 2 - Apr. 15 Solid Plantbox 2 - Apr. 15	Constant Plant-Dec 1: Addr 1: Bits Plantereditional Plantereditional Plantereditional of Plantered Plan				<form></form>




GROUND STABILIZATION AND MATERIALS HANDLING PRACTICES FOR COMPLIANCE WITH	EQUIPMENT AND VEHICLE MAINTENANCE	UNSITE CONCRETE WASHOUT STRUCTURE WITH LINER	TEMPORARY SEEDING SCHEDULE	1. OBTAIN PL
THE NCG01 CONSTRUCTION GENERAL PERMIT Implementing the details and specifications on this plan sheet will result in the construction	 Maintain vehicles and equipment to prevent discharge of fluids. Provide drip pans under any stored equipment. 		(TO TEMPORARILY STABILIZE DENUDED AREAS THAT WIL	2. FLAG LIMIT LL NOT 3. HOLD PRF-
activity being considered compliant with the Ground Stabilization and Materials Handling sections of the NCG01 Construction General Permit (Sections E and F, respectively). The	 Identify leaks and repair as soon as feasible, or remove leaking equipment from the project. 		BE BROUGHT TO FINAL GRADE FOR A PERIOD OF 15 W	/ORKING (252–946– 4. INSTALL TH
permittee shall comply with the Erosion and Sediment Control plan approved by the delegated authority having jurisdiction. All details and specifications shown on this sheet	 Collect all spent fluids, store in separate containers and properly dispose as hazardous waste (recycle when possible). 			5. INSTALL DF 6. INSTALL CC
may not apply depending on site conditions and the delegated authority having jurisdiction.	5. Remove leaking vehicles and construction equipment from service until the problem	CREARLY MARCE SIGNAR WARDUT VARAUT LATING SEVICE OF784* MINU LATING SEVICE OF784* MINU LATING SEVICE OF784* MINU LATING LIDOATEM RETERIORED IN FELD CREARLY MARCE SIGNAR LATING LIDOATEM RETERIORED IN FELD	SEEDING DATES: DECEMBER 1 THRU APRIL 15	7. INSTALL TE
SECTION E: GROUND STABILIZATION Required Ground Stabilization Timeframes	has been corrected.6. Bring used fuels, lubricants, coolants, hydraulic fluids and other petroleum products	2. THE CONCETT VARGUT STRUCTURES SHALL CONCENT VIEW THE LIBID AND/OR SELID BE WARABEE WARD AND/OR PERSONNEL CONCENT OF THE STRUCTURES SELID READERS 75% OF THE STRUCTURES CAPACITY TO PROVIDE AREAINTE CAPACITY.	SEEDING MIXTURE: <u>SPECIES</u> RAT	E. 8. PROVIDE A DAYS FOLL
Stabilize within this	to a recycling or disposal center that handles these materials.	LELE SUBJECT VANAUT STRUCTURE NEXES TO BE LEDE SUBJECT VANAUT STRUCTURE CLEWY WINGS VITH SIGNAR NOTING REVICE. NEEDE TO BE CLEWY WINGS VITH SIGNAR THIS REVICE.	(LBS/AC)	INCLUDING PERMANEN
Site Area Description many calendar Timeframe variations	LITTER, BUILDING MATERIAL AND LAND CLEARING WASTE	BELOW GRADE WASHOUT STRUCTURE ABOVE GRADE VASHOUT STRUCTURE.	RYE (GRAIN) 120	ANY PHASE 9. ADDITIONAL
Iand disturbance (a) Perimeter dikes,	 Never bury or burn waste. Place litter and debris in approved waste containers. Provide a sufficient number and size of waste containers (e.g dumpster, trash 	CONCRETE WASHOUTS	ANNUAL LESPEDEZA (KOBE) 50	STATE OR 10. AFTER SITE
swales, ditches, and 7 None perimeter slopes	receptacle) on site to contain construction and domestic wastes. 3. Locate waste containers at least 50 feet away from storm drain inlets and surface	 Do not discharge concrete or cement slurry from the site. Dispose of, or recycle settled, hardened concrete residue in accordance with local 	OMIT ANNUAL LESPEDEZA WHEN DURATION OF TEMPOR	AREAS, AN
(b) High Quality Water (HQW) Zones 7 None	waters unless no other alternatives are reasonably available. 4. Locate waste containers on areas that do not receive substantial amounts of runoff	 and state solid waste regulations and at an approved facility. 3. Manage washout from mortar mixers in accordance with the above item and in 	COVER IS NOT TO EXTEND BEYOND JUNE	EVERY 6 M
(c) Slopes steeper than If slopes are 10' or less in length and are	from upland areas and does not drain directly to a storm drain, stream or wetland. 5. Cover waste containers at the end of each workday and before storm events or	addition place the mixer and associated materials on impervious barrier and within lot perimeter silt fence.	SOIL AMENDMENTS: FOLLOW SOIL TESTS OR APPLY:	12. WITHIN 6" 13. FINE GRADI
3:1 7 not steeper than 2:1, 14 days are allowed	provide secondary containment. Repair or replace damaged waste containers.6. Anchor all lightweight items in waste containers during times of high winds.	 Install temporary concrete washouts per local requirements, where applicable. If an alternate method or product is to be used, contact your approval authority for 	2,000 LBS/AC LIMESTONE AND	14. REMOVE AL COMPLETIO
-7 days for slopes greater than 50' in length and with slopes steeper than 4:1	 Anenor an ingit weight terms in waste containers during times of high whos. Empty waste containers as needed to prevent overflow. Clean up immediately if containers overflow. 	review and approval. If local standard details are not available, use one of the two types of temporary concrete washouts provided on this detail.	750 LB/AC 10-10-10 FERTILIZER	PERM
(d) Slopes 3:1 to 4:1 14 -7 days for perimeter dikes, swales, ditches, perimeter slopes and HQW	8. Dispose waste off-site at an approved disposal facility.	 Do not use concrete washouts for dewatering or storing defective curb or sidewalk sections. Stormwater accumulated within the washout may not be pumped into or 	MULCH: 4,000 LBS/AC — ANCHOR STRAW BY TACKING ASPHALT, NETTING, OR A MULCH ANCHORING TOOL. A	a DISK <u>IN RO</u>
-10 days for Falls Lake Watershed	9. On business days, clean up and dispose of waste in designated waste containers.	discharged to the storm drain system or receiving surface waters. Liquid waste must be pumped out and removed from project.	WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL.	GA <u>M</u> S
-7 days for perimeter dikes, swales, ditches, perimeter slopes and HQW Zones	PAINT AND OTHER LIQUID WASTE 1. Do not dump paint and other liquid waste into storm drains, streams or wetlands.	 Locate washouts at least 50 feet from storm drain inlets and surface waters unless it can be shown that no other alternatives are reasonably available. At a minimum, 	MAINTENANCE: REFERTILIZE IF GROWTH IS NOT FULLY	T
flatter than 4:1 14 -10 days for Falls Lake Watershed unless there is zero slope	 Locate paint washouts at least 50 feet away from storm drain inlets and surface waters unless no other alternatives are reasonably available. 	install protection of storm drain inlet(s) closest to the washout which could receive spills or overflow.	ADEQUATE. RESEED, REFERTILIZE AND MULCH IMMEDIA FOLLOWING EROSION OR OTHER DAMAGE.	ATELY B
Note: After the permanent cessation of construction activities, any areas with temporary ground stabilization shall be converted to permanent ground stabilization as soon as	 Contain liquid wastes in a controlled area. Containment must be labeled, sized and placed appropriately for the needs of site. 	7. Locate washouts in an easily accessible area, on level ground and install a stone		<u>S</u> F
pround stabilization shall be converted to permanent ground stabilization as soon as practicable but in no case longer than 90 calendar days after the last land disturbing activity. Temporary ground stabilization shall be maintained in a manner to render the	 Containment must be labeled, sized and placed appropriately for the needs of site. Prevent the discharge of soaps, solvents, detergents and other liquid wastes from construction sites. 	entrance pad in front of the washout. Additional controls may be required by the approving authority.	<u>SEEDING DATES: APRIL 15 – AUGUST 15</u>	L
activity. Temporary ground stabilization shall be maintained in a manner to render the surface stable against accelerated erosion until permanent ground stabilization is achieved.	PORTABLE TOILETS	 Install at least one sign directing concrete trucks to the washout within the project limits. Post signage on the washout itself to identify this location. 	SEEDING MIXTURE: <u>SPECIES</u> <u>RAT</u> (LBS/AC)	<u>E</u> <u>S</u>
GROUND STABILIZATION SPECIFICATION Stabilize the ground sufficiently so that rain will not dislodge the soil. Use one of the	1. Install portable toilets on level ground, at least 50 feet away from storm drains,	 Remove leavings from the washout when at approximately 75% capacity to limit overflow events. Replace the tarp, sand bags or other temporary structural 	GERMAN MILLET	40 Č
techniques in the table below:	streams or wetlands unless there is no alternative reasonably available. If 50 foot offset is not attainable, provide relocation of portable toilet behind silt fence or place	components when no longer functional. When utilizing alternative or proprietary products, follow manufacturer's instructions.	GERMAN MILLET SOIL AMENDMENTS:	40 C
Temporary Stabilization Permanent Stabilization • Temporary grass seed covered with straw or other multiple and tackifier • Permanent grass seed covered with straw or other multiple and tackifier	on a gravel pad and surround with sand bags.2. Provide staking or anchoring of portable toilets during periods of high winds or in high	10. At the completion of the concrete work, remove remaining leavings and dispose of in an approved disposal facility. Fill pit, if applicable, and stabilize any disturbance	FOLLOW SOIL TESTS OR APPLY:	<u>S</u> F
other mulches and tackifiers other mulches and tackifiers • Hydroseeding • Geotextile fabrics such as permanent soil • Belled ergeing control products with erg • Geotextile fabrics such as permanent soil	foot traffic areas.3. Monitor portable toilets for leaking and properly dispose of any leaked material.	caused by removal of washout.	2,000 LBS/AC LIMESTONE AND 750 LB/AC 10-10 FERTILIZER	L
Rolled erosion control products with or without temporary grass seed Hydroseeding	Utilize a licensed sanitary waste hauler to remove leaking portable toilets and replace with properly operating unit.		MULCH: 4,000 LBS/AC – ANCHOR STRAW BY TACKING	; WITH
 Appropriately applied straw or other mulch Plastic sheeting Shrubs or other permanent plantings covered with mulch Uniform and evenly distributed ground cover 		HERBICIDES, PESTICIDES AND RODENTICIDES 1. Store and apply herbicides, pesticides and rodenticides in accordance with label	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS	DISK <u>M</u> S A <u>S</u>
 Uniform and evenly distributed ground cover sufficient to restrain erosion Structural methods such as concrete, asphalt or 	Show stockpile locations on plans. Locate earthen-material stockpile areas at least 50 feet away from storm drain inlets, sediment basins, perimeter sediment controls	restrictions. 2. Store herbicides, pesticides and rodenticides in their original containers with the	MULCH ANCHORING TOOL.	T B
Structural methods such as concrete, asphalt of retaining walls Rolled erosion control products with grass seed	and surface waters unless it can be shown no other alternatives are reasonably available.	label, which lists directions for use, ingredients and first aid steps in case of accidental poisoning.	MAINTENANCE: REFERTILIZE IF GROWTH IS NOT FULLY ADEQUATE. RESEED, REFERTILIZE AND MULCH IMMEDIA	TELY S
POLYACRYLAMIDES (PAMS) AND FLOCCULANTS	 2. Protect stockpile with silt fence installed along toe of slope with a minimum offset of five feet from the toe of stockpile. 	3. Do not store herbicides, pesticides and rodenticides in areas where flooding is possible or where they may spill or leak into wells, stormwater drains, ground water	FOLLOWING EROSION OR OTHER DAMAGE.	F
1. Select flocculants that are appropriate for the soils being exposed during	3. Provide stable stone access point when feasible.	or surface water. If a spill occurs, clean area immediately.4. Do not stockpile these materials onsite.	SEEDING DATES: AUGUST 15 THRU DECEMBER 15	<u>S</u>
 construction, selecting from the NC DWR List of Approved PAMS/Flocculants. Apply flocculants at or before the inlets to Erosion and Sediment Control Measures. 	 Stabilize stockpile within the timeframes provided on this sheet and in accordance with the approved plan and any additional requirements. Soil stabilization is defined and approved plan and any additional requirements. 		SEEDING MIXTURE: <u>SPECIES</u> <u>RATE (LBS/AC</u>	<u>ع</u> ۲ ۱
3. Apply flocculants at the concentrations specified in the <i>NC DWR List of Approved PAMS/Flocculants</i> and in accordance with the manufacturer's instructions.	as vegetative, physical or chemical coverage techniques that will restrain accelerated erosion on disturbed soils for temporary or permanent control needs.	HAZARDOUS AND TOXIC WASTE 1. Create designated hazardous waste collection areas on-site.		
4. Provide ponding area for containment of treated Stormwater before discharging offsite.		2. Place hazardous waste containers under cover or in secondary containment.	RYE (GRAIN) 120	<u>S(</u> F L
5. Store flocculants in leak-proof containers that are kept under storm-resistant cover or surrounded by secondary containment structures.	NORTH CAROLINA Environmental Quality	3. Do not store hazardous chemicals, drums or bagged materials directly on the ground.	SOIL AMENDMENTS: FOLLOW SOIL TESTS OR APPLY:	
			2,000 LBS/AC LIMESTONE AND 1000 LB/AC 10-10-10 FERTILIZER	A A
NCG01 GROUND S	STABILIZATION AND MATERIALS H	IANDLING EFFECTIVE: 04/01/19		R
			MULCH: 4,000 LBS/AC - ANCHOR STRAW BY TACKING	
			ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS	A DISK A
PART III SELF-INSPECTION, RECORDKEEPING AND REPORTING	PART III SELF-INSPECTION, RECORDKEEPING AND REPORTING	PART III SELF-INSPECTION, RECORDKEEPING AND REPORTING	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL.	A DISK A MAINT
	SELF-INSPECTION, RECORDKEEPING AND REPORTING	SELF-INSPECTION, RECORDKEEPING AND REPORTING	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE	A DISK A S A <u>MAINT</u> R EAS R EN IN NOTE:
SELF-INSPECTION, RECORDKEEPING AND REPORTING	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE	A DISK A S A <u>MAINT</u> R EAS R EN IN <u>NOTE:</u> COVER IN
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit.	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH	A DISK A S A <u>MAINT</u> R EAS R EN IN <u>NOTE:</u> COVER IN N LATE <u>PERM</u>
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours.	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences:	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH	A DISK A S A <u>MAINT</u> R EAS R EN IN <u>NOTE:</u> COVER IN
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more,	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2	A DISK A A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERN</u> . INSTALL NECESSARY ME SEEDING, AND COMPLETI 2. LIME AND FERTILIZER N
SELF-INSPECTION, RECORDKEEPING AND REPORTINGSELF-INSPECTIONSelf-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record.InspectFrequency (during normal business hours)	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements	SELF-INSPECTION, RECORDKEEPING AND REPORTING Image: Comparison of the section of	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1	A DISK A A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERN</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours) (1) Rain gauge maintained in Daily Daily rainfall amounts. If no daily rain gauge observations are made during weekend or	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING SECTION B: RECORDKEEPING SECTION B: RECORDKEEPING I E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measure shown on the approved E&SC plan.	SELF-INSPECTION, RECORDKEEPING AND REPORTING Image: Constraint of the second secon	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED,	A DISK A A MAINT R EAS R EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA
SELF-INSPECTION, RECORDKEEPING AND REPORTING SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Image: Frequency Inspection records must include: (1) Rain gauge Daily Daily rainfall amounts. If no daily rainfall amounts. If no daily rainfall amounts. If no daily rainfall amounts. order Daily Daily rainfall amounts. If no daily rainfall amounts. available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is Daily canade the cumulative rain measurement for those unattended days (and this will determine if a site inspection is	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING SECTION B: RECORDKEEPING SECTION Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measure shown on the approved E&SC plan. Shown on the approved E&SC plan. Finitial installation of the E&SC measures or if the E&SC measures are modified after initial	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM.	A DISK A A DISK A A MAINT R EAS R EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours.) (1) Rain gauge maintenant Daily rainfall amounts. (1) Rain gauge maintenant Daily rainfall amounts. (1) Rain gauge maintenant If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those un-	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures or if the E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume).	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 11 NEEPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH	A DISK A A DISK A A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours) (1) Rain gauge maintained in good working order Daily Daily Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per Toteme Toteme Tot the measures inspected, 2. Date and time of the inspection,	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING I. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures or if the E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL	A DISK A A DISK A A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUR
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours.) [1] Rain gauge maintained in good working order Daily [1] Rain gauge maintained in good working order Daily [2] E&SC At least once per Measures [3] Name of the person performing the inspection, 4. Indication of whether the measures were operating	SELF-INSPECTION, RECORDKEEPING AND REPORTING SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING Intervalue of the section	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND	A DISK A A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERN</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours) (1) Rain gauge maintained in good working order Daily (1) Rain gauge maintained in good working order Daily (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours of a rain event ≥ 1.0 inch in 24 hours (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours 1. Identification of the measures inspected, 2. Date and time of the inspection, 4. Indication of whether the measures were operating properly. (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours of a rain event ≥ 1.0 inch in 24 hours of a rain event ≥ 1.0 inch in 24 hours of the person performing the inspection, 4. Indication of whether the measures were operating properly. (4 hours of a calin event ≥ 1.0 inch in 24 hours of a rain event ≥ 1.0 inch in 2	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING J. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures or if the E&SC measures shown on the approved E&SC plan. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase.	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE pH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY	A DISK A A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERN</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8
SELF-INSPECTION, RECORDKEEPING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours.) (1) Rain gauge maintained in good working order Daily (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event >1 olinch in 24 hours (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event >1 olinch in 24 hours	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING J. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures or if the E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan or complete, date and sign an inspection report. (d) The maintenance and repair Complete, date and sign an inspection report.	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They cause sheen on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL.	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERN</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Irequery (during normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Inspect (during normal business hours) Daily Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those unatileded days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per 1. Identification of the measures inspection,	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING J. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to all installation. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan.	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment. 2. Reporting Timeframes and Other Requirements After a permittee becomes aware of an occurrence that must be reported, he shall contact	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE UNESTONE UNIFORMLY AND INCORPORATE	A DISK A A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERN</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours, in gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event 2 / 0. Inch in 24 hours of a rain event 2 / 0. Inch in 3. Name of the person performing the inspection, 4. Indication of whether the measures were operating properly. (3) Stormwater discharge urfalls (SDCs) At least once per 7 calendar days and within 24 hours of a rain 4. Evidence of indicators of stormwater pollution such as oil	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING JALE SEC PLAN DOCUMENTATION SECTION B: RECORDKEEPING JALE SEC PLAN DOCUMENTATION The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measure shown on the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures or if the E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (d) The maintenance and repair requirements for all E&SC measures have been performed. Complete, date and sign an inspection report. requirements for all E&SC measures have been performed. (e) Corrective acti	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They cause sheen on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 2 NEEPARATION 3 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 5 3. FERTILIZER – BASE APPLICATION RATES ON	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEX
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours) Inspection records must include: business hours) (1) Rain gauge maintained in good working order Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 linch in 24 hours 1. Identification of the measures were operating properly. (3) Stormwater discharge outfalls (SDCs) At least once per 7 calendar days and within 24 hours 1. Identification of the discharge outfalls inspection, 4. Indication of whether the measures were operating properly. (4) Perimeter of site At least once per 7 calendar days and within 24 hours 3. Name of	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING A tessed plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measures on a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (d) The maintenance and repair requires the approved E&SC measures have been performed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan.	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment. 2. Reporting Timeframes and Other Requirements After a permittee becomes aware of an occurrence that must be reported, he shall contact the appropriate Division regional office within the timeframes and in accordance with the	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 2 NEEPARATION 3 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 5 3. FERTILIZER – BASE APPLICATION RATES ON	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 6. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO
SELF-INSPECTION, RECORDKEEPING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours) Inspection records must include: business hours) (1) Rain gauge maintained in good working order Daily maintained in good working order Daily rainfail amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those un- attended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event 2 1.0 inch in 24 hours 1. Identification of the measures inspected, 1. Identification of the discharge outfalls inspection, 4. Indication of whether the measures were operating properly. (3) Stormwater discharge outfalls (SDCs) At least once per 7 calendar days and within 24 hours of a rain event 2 1.0 inch in 24 hours 1. Identification of the discharge outfalls inspection,	SELF-INSPECTION, RECORDICEEPING AND REPORTING SECTION B: RECORDICEEPING SECTION B: RECORDICEEPING A E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measure on a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate complance with approved ground cover specifications. (d) The maintenance and repair requirements for all E&SC measures complete, date and sign an inspection report. (e) Corrective actions have been taken to E&SC measures. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report. (e) Corrective actions have been taken to E&SC measures. <td< td=""><td>SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.5. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment. After a permittee becomes aware of an occurrence that must be reported, he shall contact the appropriate Division regional office within the timeframes and in accordance with the other requirements listed below. Occurrences outside normal business hours may also be reported to the Department's Environmental Emergency Center personnel at (800)</td><td>ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 5. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH</td><td>A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN G. COMPLETE SEEDBED PR</td></td<>	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.5. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment. After a permittee becomes aware of an occurrence that must be reported, he shall contact the appropriate Division regional office within the timeframes and in accordance with the other requirements listed below. Occurrences outside normal business hours may also be reported to the Department's Environmental Emergency Center personnel at (800)	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 5. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN G. COMPLETE SEEDBED PR
SELF-INSPECTION, RECORDKEEPING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect frequency (diving normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. (1) Rain gauge maintained in good working order Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per 7 calendar days and whith 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of a rain event ≥ 1.0 linch in 24 hours of the spacomed solidis or discolaration, 5. Indication of visib	SELF-INSPECTION, RECORDICEPING AND REPORTING SECTION B: RECORDICEPING Jan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevetions and relative elevetions shown on the approved E&SC plan. Initial and date each E&SC measures or if the E&SC measures or if the E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed installed installed incacordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (d) The maintenance and repair requirements for all E&SC measures have been taken to E&SC measures. Complete, date and sign an inspection report. (e) Corrective actions have been taken to E&SC measures. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report. (e) Corrective actions have been taken to E&SC measures. Initial and d	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They are steen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment. CReporting Timeframes and Other Requirements After a permittee becomes aware of an occurrence that must be reported, he shall contact the appropriate Division regional office within the timeframes and in accordance with the other requirements listed below. Occurrences outside normal	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE pH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES ON SOIL TESTS. WHEN THESE ARE NOT 6 POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 6. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE
SELF-INSPECTION, RECORDKEEPING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect frequency (dring normal business hours) Inspection records must include: business hours) (1) Rain gauge maintained in good working order Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those un- attended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per and within 24 hours of a rain event ≥ 1.0 linch in 24 hours 1. Identification of whether the measures inspected, 3. Name of the person performing the inspection, 4. Indication of whether the measure pollution such as oil sheen, floating or suspended solids or discorration, 5. Indication of storm water pollution such as oil sheen, floating or suspended solids or discorration, 5. Indication of storm water pollution such as oil sheen, floating or suspended solids or discorration, 5. Indication of storm water pollution such as oil sheen, floating or suspended solids or discorration, 5. Indication of storm water pollution such as oi	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING I tass of plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan. Initial and date each E&SC measures on a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report the indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (d) The maintenance and repair require complete, date and sign an inspection report. (e) Corrective actions have been taken to E&SC measures. Complete, date and sign an inspection report. (e) Corrective actions have been taken to E&SC measures. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report. (e) Corrective act	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are subsen on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE pH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A pH OF 6 OR HIGHER NEED NOT BE LIMED. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL. IF A HYDRAULIC SEEDER IS USED, DO NOT MIX SEED AND FERTILIZER	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE PERM INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTUF SCHEDULE ON THIS SHE GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTIL DISKING OR OTHER SUIT S. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDKEEPING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect frequency (during normal business hours) Inspection records must include: business hours) (1) Rain gauge maintained in good working order Daily Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those un- attended days (ant this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero". The permittee may use another rain-monitoring device approved by the Division. (2) E&SC Measures At least once per 7 calendar days and within 24 hours of a rain event 2.10 inch in 24 hours 1. Identification of the measures inspection, 3. Name of the person performing the inspection, 4. Indication of wisher sediment leaving the site, 6. Description, evidence, and date of corrective actions taken. 4. Evidence of indicators of stormwater pollution such as oil sheen, floating or suspended solidis or discoloration, 3. Indication of visible sedimentalism is found outside site limits, the	SELF-INSPECTION, RECORD CEPING AND REPORTING SECTION 5: RECORD MEEPING JEND COLSPICE SECTION SE	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are less than 25 gallons but cannot be cleaned up within 24 hours, • They cause sheen on surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment. After a permittee becomes aware of an occurrence that must be reported, he shall contact the appropriate Division regional office within the timeframes and in accordance with the other requirements listed below. Occurrence soutside normal business hours may also be reported to the Department's Environmental Emergency Center personnel at (800) s58-0368. Occurrence Reporting Timeframes (After Discovery) and Other Requirements for a written report on a case-by-case basis. (a) Visible sediment and action taken to address the cause of the deposition. Division staff may waike the requirement for a written report on a case-by-case basis. <	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROGE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 5 . FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH FERTILIZER AT 700 – 1000 LB/ACRE. BOTH	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 6. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE
SELF-INSPECTION, RECORDKEEPING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect frequency (uning normal business hours) Inspection records must include: business hours) (1) Rain gauge porder Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual day rainfall information is available, record the cumulative rain measurement for those un- attended days (and this will determine if a site inspection is needed). Days on which no rainfall occured shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division. (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event 2.1.0 inch in 24 hours 1. Identification of the measures were operating properly. (3) Stormwater discharge outfalls (SDCs) At least once per 7 calendar days and within 24 hours of a rain event 2.1.0 inch in 24 hours 1. Datern time of the inspection, 3. Name of the person performing the inspection, 3. Name of the person performing the inspection, 3. Name of the person performing the inspection, 3. Name of the person date of corrective actions taken.	SELF-INSPECTION, RECORD CALCEPING AND REPORTING SECTION B: RECORD KEEPING SECTION B: RECORD KEEPING Data Section 2012 SECTION B: RECORD KEEPING SECTION B: RECORD KEEPING Data Section 2012 Section 2012 Data Section 2012 Section 2012 Decomposition of the times during normal business hours. Term to Document Documentation Requirements Initial and date each E&SC measure on a copy of the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measures shown on the approved E&SC plan. Initial and date a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan or complete, date and sign an inspection report. (d) The maintenance and repair requirements for all E&SC measures in	SELF-INSPECTION, RECORDKEEPING AND REPORTING SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1 Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are so that 25 gallons but cannot be cleaned up within 24 hours, • They are so that 26 gallons but cannot be cleaned up within 24 hours, • They are so that 26 gallons but cannot be cleaned up within 24 hours, • They are so that 26 gallons but cannot be cleaned up within 24 hours, • They are so that 26 gallons but cannot be cleaned up within 24 hours, • They are so that 200 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or GS. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROCE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE pH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH FERTILIZER AT 000 – 1000 LB/ACRE. BOTH FERTILIZER AT 700 – 1000 LB/	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE PERM INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTUF SCHEDULE ON THIS SHE GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTIL DISKING OR OTHER SUIT S. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDKEEPING AND REPORTING SET-INSPECTION SET-INSPECTION Self-Inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (during normal business hours) Inspection records must include: business hours) [1] Nam gauge maintained in good working order Daily Inspection records must include: business hours) [2] E&SC At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours of a rain event ≥ 1.0	SELF-INSPECTION, RECORD CAREPING AND REPORTING SECTION B: RECORD KEEPING Jack Colspan Base and Sany approved deviation shall be kept on the site. The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Image: the temperature of the temperature of the approved E&SC plan shall be kept on site and available for inspection, admensions and relative elevations of the approved E&SC plan complete, date and sign an inspection report that lists each E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan or complete, date and sign an inspection report to indicate complete and with approved E&SC plan or complete, date and sign an inspection report to indicate complete and with approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accory of the approved E&SC plan or complete, date and sign an inspection report. To indicate compliance with approved E&SC plan or complete, date and sign an inspection report to indicate tomplane. (d) The maintenance and repair requirements for all E&SC measures in a d	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1 Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are 25 gallons or more, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons or more, • They are so than 25 gallons but cannot be cleaned up within 24 hours, • They are so than 25 gallons but cannot be cleaned up within 24 hours, • They are within 100 feet of surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROCE MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND ACRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL. IF A HYDRAULC SEEDER IS USED, DO NOT MIX SEED AND FERTILIZER MORE THAN 30 MINUTES BEFORE APPLICATION. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITONAL ROUGHENING	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE PERM INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 6. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. SITE AREA DESCRI
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect ferugency maintained in good working order Inspection records must include: H no daily rain gauge observations are made during weekend or holiday periods, and no individanday rainfall information is available, record the cumulative rain measurement for thoses un- attended days (and this will determine if a site inspection is needed). Days on which no rainfall cocurned shall be recorded as "zero". The permittee may use another rain-monitoring device aproved by the Division. [2) E&SC At least once per 7 calendar days and within 24 hours of a rain event 2.1.0 inch in 24 hours 1. Identification of the inspection, 8. Name of the person performing the inspection, 9. Description, evidence, and date of corrective actions taken. [4) Perimeter of site At least once per 7 calendar days and within 24 hours of a rain event 2.1.0 inch in 24 hours Name of the person performing the inspection, 9. Description, evidence, and date of corrective actions taken. [5) Streams ar wettands onsite or offsite wettand sonsite o	SELF-INSPECTION, RECORDECEPING AND REPORTING SECTION B: RECORDECEPING SECTION B: RECORDECEPING SECTION B: RECORDECEPING SECTION B: RECORDECEPING Subscript and sevel as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document Documentation Requirements (a) Each E&SC measure on a copy of the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measures or if the E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report. (d) The maintenance and repair require complance with approved E&SC measures in accordance w	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1 Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: • They are 25 gallons or more, • They are 25 gallons or more, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons but cannot be cleaned up within 24 hours, • They are 25 gallons or more, • They are so than 25 gallons but cannot be cleaned up within 24 hours, • They are so than 25 gallons but cannot be cleaned up within 24 hours, • They are within 100 feet of surface waters (regardless of volume), or • They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses. (e) Noncompliance with the conditions of this permit that may endanger health or the environment.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL. IF A HYDRAULIC SEEDER IS USED, DO NOT MIX SEED AND FERTILIZER MORE THAN 30 MINUTES BEFORE APPLICATION. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITIONAL ROUGHENING MAY NOT BE REQUIRED, EXCEPT TO BREAK UP LARGE CLODS. IF RAINFALL CAUSES	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE PERM INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTI DISKING OR OTHER SUIT DISKING OR OTHER SUIT S. COMPLETE SEEDBED PR UNIFORM SURFACES IN S. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. SITE AREA DESCRI PERIMETER DIKES, SWALES, HIGH QUALITY WATER (HQM
SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION A: SELF-INSPECTION Self-Inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect Frequency (uming normal business hours) Inspection records must include: husiness hours) (1) Rain gauge maintained in good working Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those un- attended day; (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero". The period the measures uncher rain-montoring device approved by the Division. (2) E&SC At least once per 7 calendar days and within 24 hours of a rain event 2.1 0 inch in 24 hours Name of the person performing the inspection, 4. Indication of whether the measures we operating properly. (3) Stormwater discharge outfalls (SDCs) At least once per 7 calendar days and within 24 hours of a rain event 2.1 0 inch in 24 hours Name of the person performing the inspection, 4. Indicatind or visible sedimentation is found dusifi	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Image: The two Document is the E&SC plan shall be kept on site and available for inspection significantly deviate from the locations, dimensions and relative elevations is align an inspection report that lists each E&SC measure shown on the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures are modified after initial installation of the E&SC measures are modified after initial installation of the E&SC measures or if the E&SC measures are modified after initial installation of the E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (d) The maintenance and repair requirements for all E&SC plan and cover specifications. (e) Corrective actions have been taken intial and date a copy of the approved E&SC plan an inspection report. Trequirements for all E&SC measures how no run indicate the completion of the corrective action. Addition to the E&SC plan complete, date and sign an inspection report. Trequirements for all E&SC plan coremplete, date and sign an inspection repor	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are sets than 25 gallons but cannot be cleaned up within 24 hours, They are sets than 25 gallons our date waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, 'NETTING,' OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL 3 TEST RECOMMENDATIONS. IF THE pH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND ACRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A pH OF 6 OR HIGHER NEED NOT BE LIMED. 5 S FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT 700 – 1000 LB/ACRE. BOTH FERTILIZER AT 700 – 1000 LB/ACRE. BOTH FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL. IF A HYDRAULIC SEEDER IS USED, DO NOT MIX SEED AND FERTILIZER MORE THAN 30 MINUTES BEFORE APPLICATION. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITONAL ROUGHENING MAY NOT BE REQUIRED, EXCEPT TO BREAK UP LARGE CLODS. IF RAINFALL CAUSES THE SURFACE TO BECOME SEALED OR CRUSTED, LOOSEN IT JUST PRIOR TO	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE PERM INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTI DISKING OR OTHER SUIT S. COMPLETE SEEDBED PR UNIFORM SURFACES IN COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. SITE AREA DESCRI
SELF-INSPECTION Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Inspect foruing normal business hours, the self-inspection shall be gord working or holding perdox for the commutation is admittained in good working or holding perdox, for the spectrom record measures inspected. (1) Rain gauge Delay Daily rainfall amounts. (1) Rain gauge Delay Daily rainfall amounts. (1) Rain gauge Delay Daily rainfall amounts. (2) E&SC At least once per 1. destification of the measures inspected. (2) E&SC At least once per 1. destification of the measures were operating error by and whith 24 hours 4. Donkin 124 hours 4. Donki	SELF-INSPECTION, RECORDECEPING AND REPORTING SECTION B: RECORDECEPING LESC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. (a) Each E&SC measure has been installed and date each E&SC measure on a copy of the approved E&SC plan or complete, date and sign an inspection report that list each E&SC measures and relative elevetrons of sign in inspection report the list each E&SC measures and relative elevetrons ing sign in inspection report the list each E&SC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved E&SC plan or complete, date and sign an inspection report to indicate the compliance with approved E&SC plan or complete, date and sign an inspection report. The infact and the a copy of the approved E&SC plan. (c) Ground cover is located and installed in a complete, date and sign an inspection report. To indicate compliance with approved E&SC plan or complete, date and sign an inspection report. To indicate the compliance with approved E&SC plan or complete, date and sign an inspection report. To indicate t	SELF-INSPECTION, RECORDICEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills ff: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are use sheen on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 10.2 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NEOESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 2 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE pH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS WITH A pH OF 6 OR HIGHER NEED NOT BE LIMED. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL. IF A HYDRAULIC SEEDER IS USED, DO NOT MIX SEED AND FERTILIZER MORE THAN 30 MINUTES BEFORE APPLICATION. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITIONAL ROUGHENING MAY NOT BE REQUIRED, EXCEPT TO BREAK UP LARGE CLODS. IF RAINFALL CAUSES THE SURFACE TO BECOME SEALED OR CRUSTED, LOSSEN IT JUST PRIOR TO SEEDING BY DISKING, RAKING, HARROWING, OR OTHER SUITABLE METHODS. GROOVE	A DISK A A MAINT R A MAINT R EAS EN IN NOTE: COVER IN N LATE PERM INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTI DISKING OR OTHER SUIT DISKING OR OTHER SUIT S. COMPLETE SEEDBED PR UNIFORM SURFACES IN S. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. SITE AREA DESCRI PERIMETER DIKES, SWALES, HIGH QUALITY WATER (HQM
<section-header><section-header><section-header><section-header><text></text></section-header></section-header></section-header></section-header>	SELF-INSPECTION, RECORDKEEPING AND REPORTING SECTION B: RECORDKEEPING 1. E&SC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Image: The two Document is the E&SC plan shall be kept on site and available for inspection significantly deviate from the locations, dimensions and relative elevations is align an inspection report that lists each E&SC measure shown on the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures are modified after initial installation of the E&SC measures are modified after initial installation of the E&SC measures or if the E&SC measures are modified after initial installation of the E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (c) Ground cover is located and installed in accordance with the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase. (d) The maintenance and repair requirements for all E&SC plan and cover specifications. (e) Corrective actions have been taken intial and date a copy of the approved E&SC plan an inspection report. Trequirements for all E&SC measures how no run indicate the completion of the corrective action. Addition to the E&SC plan complete, date and sign an inspection report. Trequirements for all E&SC plan coremplete, date and sign an inspection repor	SELF-INSPECTION, RECORDICEEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are uses sheen on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref. 40 CFR 10.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 4 SOILS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 NOT BE LIMED. 3. FERTILIZER AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF THE SOIL SULS WITH A PH OF 6 OR HIGHER NEED NOT BE LIMED. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITIONAL ROUGHENING MAPPLICATION. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITIONAL ROUGHENING MAPY NOT BE REQUIRED, EXCEPT TO BREAK UP LARCE CLODS. IF RAINFALL CAUSES THE SURFACE TO BECOME SEALED OR CRUSTED, LOOSEN IT JUST PRIOR TO SEEDING BY DISKING, RAKING, HARROWING, OR OTHER SUITABLE METHODS. GROOVE OR FURROW SLOPES STEEPER THAN 3:1 ON THE CONTOUR BEFORE SEEPER THAN 3:1 ON THE CONTOUR BEFORE SEEPER THAN 3:1 ON	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> INSTALL NECESSARY ME SEEDING, AND COMPLET LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI A APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. SLOPES STEEPER THAN 3:1
SELF-INSPECTION, RECORDECEPING AND REPORTING Self-Inspections are required during normal business hours in accordance with the table personnel to be in jopedrafy, the inspection may be delayed until the next business day on greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business hours, the self-inspection shall be performed upon the commencement of the next business hours, the self-inspection shall be performed upon the commencement of the next business hours, the self-inspection shall be next business hours, the self-inspection shall be next business hours, the self-inspection shall be neaded shall be next business hours, the self-inspection set of the next business hours, the inspection is available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is needed). Days on which no rainfall ourserving is neaded uning weekend or holiday periods, and no individual day rainfall information is needed. Davis on which no rainfall ourserving is neaded uning weekend or holiday periods, and no individual day rainfall information is needed. Davis on which no rainfall outserving is neaded or the neasure end of a rain or the period period byte. Divisio. (2) E&SC At least once perf indication of the messures inspected. Hours of a rain or the period performing the inspection. (3) Stormwater At least once performed in the disdarg our dividual singetcet. Or indication of whithe addition or unable astimution such as ol is dividual to a rain or the inspection. (4) Perimeter of at least once performing the inspection. Davis of a rain or the inspection. (5) Stormwater At least once performing the inspectio	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION 3: RECORDREEPING LASC Plan Documentation The approved E&SC plan as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. Item to Document (a) Each E&SC measure has been installed and sign an inspection report that lists each E&SC measures and relative elevations is an inspection report that lists each the ESC measures are modified after initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan. This documentation is required upon the initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan. This documents in the approved E&SC measures are copy of the approved E&SC plan. This documents for all E&SC measures in complete, date and sign an inspection report. (c) Ground cover is located and installed plan or complete, date and sign an inspection report. (d) The maintenance and repair (e) Corrective actions have been taken (b take and sign an inspection report. (b take and available for inspectors on the take complete, date and sign an inspection report. (b taddition to the E&SC plan documents above, t	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION C: REPORTING I Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are selesn on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or 6.5. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOF MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1. A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2–3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER A TOO – 1000 LB/ACRE. BOTH FERTUARE AT THERE ARE NOT OSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES ON SOIL TESTS. WHEN THESE ARE NOT POSSIBLE APPLY A 10–10–10 GRADE FERTILIZER AT AND LIME SHOULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL. IF A HORAULD BE INCORPORATED INTO THE TOP 4–6 INCHES OF SOIL IF A NOT MIX SEED AND FERTILIZER MORE THAN 30 MINUTES BEFORE APPLICATION. 4. SURFACE ROUGHENING – IF RECENT TILLAGE OPERATIONS HAVE RESULTED IN A LOOSE SURFACE, ADDITIONAL ROUGHENING MAY NOT BE REQUERD, EXCEPT TO BREAK UP LARGE CLODS. IF RAINFALL CAUSES THE SURFACE TO BECOME SEALED OR CRUSTED, LOOSEN IT JUST PRIOR TO SEEDING BY DISKING, RAKING, HARROWING, OR THER SUITABLE METHODS. GROOVE OR FURROW SLOPES STEEPER THAN 3:1 ON	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDECEPING AND REPORTING Self-Inspections are required during normal business hours in accordance with the table personnel to be in jopedrafy, the inspection may be delayed until the next business day on greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business hours, the self-inspection shall be performed upon the commencement of the next business hours, the self-inspection shall be performed upon the commencement of the next business hours, the self-inspection shall be next business hours, the self-inspection shall be next business hours, the self-inspection shall be neaded shall be next business hours, the self-inspection set of the next business hours, the inspection is available, record the cumulative rain measurement for those unattended days (and this will determine if a site inspection is needed). Days on which no rainfall ourserving is neaded uning weekend or holiday periods, and no individual day rainfall information is needed. Davis on which no rainfall ourserving is neaded uning weekend or holiday periods, and no individual day rainfall information is needed. Davis on which no rainfall outserving is neaded or the neasure end of a rain or the period period byte. Divisio. (2) E&SC At least once perf indication of the messures inspected. Hours of a rain or the period performing the inspection. (3) Stormwater At least once performed in the disdarg our dividual singetcet. Or indication of whithe addition or unable astimution such as ol is dividual to a rain or the inspection. (4) Perimeter of at least once performing the inspection. Davis of a rain or the inspection. (5) Stormwater At least once performing the inspectio	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION 3: RECORDREEPING SECTION 3: RECORDREEPING Colspan= as well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan shall be kept on site and available for inspection at all times during normal business hours. tem to Document Documentation Requirements and sign an inspection report that lists each E&SC measures on a copy of the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measures are modified after initial initial installation. (b) A phase of grading has been completed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report. (c) Ground cover is located and installed Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved ground cover specifications. (d) The maintenance and repair requirements for all E&SC measures have been performed. Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate the completion of the Comport to indicate the completion shall be kept on the site requirements for all E&SC measures have been performed. <t< td=""><td>SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittices shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are set shan 25 gallons but cannot be cleaned up within 24 hours, They are within 100 feet of surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 10.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.</td><td>ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE</td><td>A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.</td></t<>	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittices shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are set shan 25 gallons but cannot be cleaned up within 24 hours, They are within 100 feet of surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 10.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDECEPTING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection proving the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be provided shall be noted in the Inspection Record. New etable of the result of the next business day. Any time when inspections are reade used in the Inspection Record. New etable of the inspection record must induce: New etable of the inspection record must induce: New etable of the inspection are made during weekend or holdwidad day (and this will determine if a ste inspection is valiable, record the cumulative rain measurement for those unstantianed in the inspection. (2) EASC A least one per 1 (1) Rein grave the or particular day: (1) Rein grave the particular day: (1) Rein grave the or particular day: (1) Rein grave the or particular day: (1) Rein grave the or particular day: (1) Rein grave the resource the resourc	SELFINSPECTION, RECORDEREPTING SECTION STATEMENT Statem	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittives shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They cause sheen on surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 10.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDECEPTING AND REPORTING Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection presonnel to be in jeopardy, the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections user delayed shall be noted in the inspection Record. Impact fermionic inspection Record (1) Rain gauge baily inspection Record (2) EBSC R least one per domination of the messurement for those unstantaned in good working inspection Record (2) EBSC R least one per domination of the inspection is precised. inspection Record (3) Starmwater A least one per domination of the inspection. in addition of the inspection. (3) Starmwater A least one per domination of the inspection. in addition of the inspection. (4) Perimeter of A least one per domination of the inspection. in addition of the inspection. in addition of the inspection. (5) Starmwater A least one per domination of the inspection. in addition of the inspection. in addition of the inspection. (3) Starmwater A least one per domination of the inspection. in addition of the inspection. in addition o	SELF-INSPECTION, RECORDEREPTING AND REPORTING SECTION SECTION RECORDEREPTING DATE OF COLSPANS AND	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION C: REPORTING Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gailons or more, They are 25 gailons or more, They are 25 gailons or more, They are exist than 25 gailons but cannot be cleaned up within 24 hours, They are within 100 feet of surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 110.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or 6.5. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDCEEPING AND REPORTING Self-Inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection way be delayed until the next business day on when a storm event of equal to or greater than 1.0 nch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record. Imspect Temperation in the inspection Record. (1) Ann gauge Daily rainal amounts. Imspect Temperation Record. (1) Ann gauge Daily rainal amounts. Intractined in good working Daily rainal amounts. (1) Ann gauge Daily rainal amounts. Intractined in good working Daily rainal amounts. (2) E&SC At least once per 7 (2) E&SC A least once per 7 (3) Bornewer 1 identification of the measures impacted. (2) E&SC A least once per 7 (3) Bornewer 2 to find in internace needs for the measures. 1 identification of whether the measures. (2) E&SC A least once per 7 (3) Bornewer 2 to find in internace needs for the measures. 1 identification of whether the measures. (2) E&SC A least once per 7	SELF-INSPECTION, RECORDECEPING AND REPORTING SECTION 5: RECORDECEPING Section 5: Record December 3: Section 5: Record Colspan= 3: Section 7: Record Colspan=	SELF-INSPECTION, RECORDREEPING AND REPORTING SECTION C: REPORTING 1. Occurrences that Must be Reported Permittives shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills if: They are 25 gallons or more, They are 25 gallons or more, They are less than 25 gallons but cannot be cleaned up within 24 hours, They are within 100 feet of surface waters (regardless of volume), or They are within 100 feet of surface waters (regardless of volume). (c) Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 10.3 and 40 CFR 117.3) or Section 102 of CERCLA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (d) Anticipated bypasses and unanticipated bypasses.	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDCEEPING AND REPORTING Self-Inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection safe to perform the inspection. In addition, when a storm event of equal to or gradient than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection. In addition, when a storm event of equal to or gradient during weather and in the inspection. In addition, when a storm event of equal to or gradient during weather and inspection second uses and when a storm event of equal to or gradient during weather and inspections are made during weather or holiday periods, and no individual day reliafil information is available, record the cumulative rain measurement for those uses and the period method day faint and the inspection. The gradient day reliafil alter and the addition of a rain inspection is inspection; and whether an mentioning device approved by the Division. (2) ESS At least once per to the period on period gradient day in a start of the inspection. (3) Stormward At least once per to the period gradient day in the start on the period gradient day in the start and the or the researce. (4) Period on the period gradient day in the start of the inspection. base and time of the inspection. base and time of the inspection. base and the or the researce. base and the or the researce. base and time of the inspection. base and tinse of the inspection. base a	SELF-INSPECTION, RECORDCEEPING AND REPORTING SECTION 5: RECORDCEEPING INERCORDCEEPING INERCORDCEEPING INERCORDCEEPING	<section-header><section-header><section-header></section-header></section-header></section-header>	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDCEEPING AND REPORTING SetTions are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection shall be below. When adverse weather or site conditions would cause the safety of the inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the inspection. In addition, when a storm every delayed shall be noted in the inspection. In addition, when a storm every delayed shall be noted in the inspection records must include: Inspect forgung promoting provide during the next business day. Any time when inspections were delayed shall be noted in the inspection. In addition, whether alin measurement for those watered days (and the inspection ecords neutrino the material information in an attended days (and the inspection ecords neutrino the inspection is needed). During the neutrino the inspection records neutrino the inspection is needed. During weakend on the inspection of the instance inspection is needed. During weakend on the instance internet is a site inspection is needed. During weakend on the instance inspection is needed. During weakend on the instance inspection. (3) Stormwater At least once per A called and the of corrective addition and the inspection. 1. Identification of the measures improved. (4) Perimeter of At least once per A called and the of corrective addition of a anit in the inspection. 1. Identification of the instance inspection. (4) Perimeter of At least once per A called addition of the instance instance. 1. Identification of the instance output of the insthem a correction of the instance output of the instance	SELF-INSPECTION, RECORDCEEPING AND REPORTING SECTION 5: RECORDCEEPING INERCORDCEEPING INERCORDCEEPING INERCORDCEEPING	<section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header>	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDCEPING AND REPORTING SETION SET REQUIRED during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection spectrom may be delayed until the next business day on year of the inspection. In addition, when a storm event of equal to or year of the inspection. In addition, when a storm event of equal to or year of the inspection. In addition, when a storm event of equal to performed upon the commencement of the next business day. Any time when inspections are relayed shall be noted in the Inspection. In addition, whether an inspectimement for those using addition of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection of institution is the ast ordinate read the inspection. The ordinate read the inspection of institution is the ordinate read the inspection. The ordinate read the inspection of institution of the ordinate ordinate inspection of institution of the inspection of institution of the ordinate inspection. The ordinate read the inspection of institution of the ordinate ordinate institutis in a constitution of the ordinate ordinate	SELF-INSPECTION, RECORDIGEPING AND REPORTING SECTION 5: RECORDIGEPING Colspan="2">Section at all times a well as any approved deviation shall be kept on the site. The approved E&SC plan must be kept on site and available for inspection at all times during normal business hours. (a) Each E&SC measure has been installed to inspection at all times during normal business hours. (b) Each E&SC measure has been installed to installed to inspection apport the table well table approved E&SC plan or complete, date and sign an inspection report the installation. (b) A phase of grading has been completed. Base E&SC measure and effect and sign an inspection report. (c) Ground cover is located and installed to installed the approved E&SC plan. This documentation is required upon the hist and accord and the approved E&SC plan or complete, date and sign an inspection report. (c) Ground cover is located and installed to installed the approved E&SC plan or complete, date and sign an inspection report. (d) The maintenance and repair installation. Initial and date a copy of the approved E&SC plan accomplete. (e) Corrective actions have been taken bin in table and date a copy of the approved E&SC plan or complete, date and sign an inspection report. (e) Corrective actions have been taken binking and date a copy of the approved E&SC plan documents above, the following items shall be kept on the stead available for inspections. (d) The maintenance and repair requirements for al E&SC measures. Complete, date and sign an inspection report.	<section-header> Set-Inspectron, RECORDECPING AND REPORTING SETCION C: REPORTINE 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills iff: 1. They are less than 25 gallons but cannot be cleaned up within 24 hours, 1. They are less than 25 gallons but cannot be cleaned up within 24 hours, 1. They are ass than 25 gallons or more, 1. They are ass than 25 gallons or more, 1. They are ass than 25 gallons or more, in the clean waters (regardless of volume), or 1. Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 1012, and 40 CFR 117.3) or Section 102 of CERCIA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (a) Anticipated bypasses and unanticipated bypasses. After a permittee becomes aware of an occurrence that must be reported, he shall contact the anyportate Division regional office within the timeframes and in accordance with the environment. Streament and the streament is further 24 hours, an oral or electronic notfleaton. (b) Visite 2 divisite 3 hours, an oral or electronic notfleaton. (b) Visite 2 divisite 3 hours, an oral or electronic notfleaton. (c) Visite 2 hours, an oral or electronic notfleaton. (d) Visite 2 hours, an oral or electronic notfleaton. (e) Visite</section-header>	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.
SELF-INSPECTION, RECORDCEPING AND REPORTING SETION SET REQUIRED during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection spectrom may be delayed until the next business day on year of the inspection. In addition, when a storm event of equal to or year of the inspection. In addition, when a storm event of equal to or year of the inspection. In addition, when a storm event of equal to performed upon the commencement of the next business day. Any time when inspections are relayed shall be noted in the Inspection. In addition, whether an inspectimement for those using addition of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection. The ordinate read the inspection of institution of the inspection of institution is the ast ordinate read the inspection. The ordinate read the inspection of institution is the ordinate read the inspection. The ordinate read the inspection of institution of the ordinate ordinate inspection of institution of the inspection of institution of the ordinate inspection. The ordinate read the inspection of institution of the ordinate ordinate institutis in a constitution of the ordinate ordinate	SELF-INSPECTION, RECORDECEPING AND REPORTING SECTION 5: RECORDECEPING LASC Flan Documentation The proved E&SC plan must be kept up-to-date throughout the coverage under this permit. The following items pertaining to the E&SC plan sholl be kept on site and available for inspection at all times during normal business hours. Image:	<section-header> Set-Inspectron, RECORDECPING AND REPORTING SETCION C: REPORTINE 1. Occurrences that Must be Reported Permittees shall report the following occurrences: (a) Visible sediment deposition in a stream or wetland. (b) Oil spills iff: 1. They are less than 25 gallons but cannot be cleaned up within 24 hours, 1. They are less than 25 gallons but cannot be cleaned up within 24 hours, 1. They are ass than 25 gallons or more, 1. They are ass than 25 gallons or more, 1. They are ass than 25 gallons or more, in the clean waters (regardless of volume), or 1. Releases of hazardous substances in excess of reportable quantities under Section 311 of the Clean Water Act (Ref: 40 CFR 1012, and 40 CFR 117.3) or Section 102 of CERCIA (Ref: 40 CFR 302.4) or G.S. 143-215.85. (a) Anticipated bypasses and unanticipated bypasses. After a permittee becomes aware of an occurrence that must be reported, he shall contact the anyportate Division regional office within the timeframes and in accordance with the environment. Streament and the streament is further 24 hours, an oral or electronic notfleaton. (b) Visite 2 divisite 3 hours, an oral or electronic notfleaton. (b) Visite 2 divisite 3 hours, an oral or electronic notfleaton. (c) Visite 2 hours, an oral or electronic notfleaton. (d) Visite 2 hours, an oral or electronic notfleaton. (e) Visite</section-header>	ASPHALT, NETTING, OF A MULCH ANCHORING TOOL. A WITH BLADES SET NEARLY STRAIGHT CAN BE USED AS MULCH ANCHORING TOOL. MAINTENANCE: REPAIR AND REFERTILIZE DAMAGED ARE IMMEDIATELY. TOPDRESS WITH 50 LBS/AC OF NITROOG MARCH. IF IT IS NECESSARY TO EXTEND TEMPORARY BEYOND JUNE 15, OVERSEED WITH 50 LBS/AC KOBE IN FEBRUARY OR EARLY MARCH 1 TEMPORARY SEEDBED 2 PREPARATION 1 A GOOD SEEDBED IS WELL PULVERIZED, LOOSE, AND UNIFORM. 2. LIMING – APPLY LIME ACCORDING TO SOIL TEST RECOMMENDATIONS. IF THE PH (ACIDITY) OF THE SOIL IS NOT KNOWN, AN APPLICATION OF GROUND AGRICULTURAL LIMESTONE AT THE RATE OF 1 – 1.5 TONS/ACRE ON FINE TEXTURED SOILS AND 2 – 3 TONS/ACRE ON COARSE TEXTURED SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. SOILS IS USUALLY SUFFICIENT. APPLY LIMESTONE UNIFORMLY AND INCORPORATE INTO THE TOP 4–6 INCHES OF THE SOIL. 3. FERTILIZER – BASE APPLICATION RATES ON SOIL TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOILS TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 6 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 8 SOIL TESTS. WHEN THESE ARE NOT 7 SOIL TESTS. WHEN THESE ARE NOT 7 SEEDING BY DISKING, RAKING, HARROWING 7 SEEDING BY DISKING, RAKING, HARROWING 7 OR THER SUITABLE METHODS. GROOVE 7 OR FURROW SLOPES STEEPER THAN 3:1 ON 7 HE CONTOUR BEFORE SEEDING. SEE 7 OTHER REQUIREMENTS FOR SURFACE	A DISK A A MAINTI R A MAINTI R EAS EN IN NOTE: COVER IN N LATE <u>PERM</u> . INSTALL NECESSARY ME SEEDING, AND COMPLET 2. LIME AND FERTILIZER N PERFORMED FREE OF CH DIRECTIONS, SAMPLE CA EXTENSION OFFICES OR WEEKS FOR SAMPLE TUI GRADING. TESTING IS A 3. WHEN SOIL TESTS ARE SCHEDULE ON THIS SHE GROUND AGRICUL LIGHT TEXTUF HEAVY TEXTU FERTILIZER: GRASSES: 8 GRASS-LEGUI 4. APPLY LIME AND FERTI DISKING OR OTHER SUIT 5. ROUGHEN SURFACES IN 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL. 5. COMPLETE SEEDBED PR UNIFORM SURFACE (SLO WATER. BROADCAST SE RAINFALL.

13		14	15				
CONST	RUCTION	SCHEDULE		GENE	eral notes		
AIN PLAN APPROVALS AND 5 LIMITS OF ROUGH GRADING 9 PRE-CONSTRUCTION MEET	Э.						
-946-6481), PROJECT ENG ALL THE PERIMETER SEDIME ALL DRIVEWAY PIPE AND TE	SINEER, AND OW INT FENCES AS	VNER BEFORE WORK BEGIN THE FIRST CONSTRUCTIO	NS. N ACTIVITY.				м
ALL CONCRETE WASHOUT A ALL TEMPORARY SEDIMENT	REA WITH SIGN. BASIN AND TEN	MPORARY DIVERSION SWAI	le per plan.				
/IDE A GROUND COVER (TEI S FOLLOWING COMPLETION C JDING ALL OTHER SLOPES	OF ANY PHASE	OF GRADING FOR SLOPES	5 3:1 OR FLATTER				
IANENT) ON EXPOSED SLOF PHASE OF GRADING FOR S TIONAL EROSION AND SEDIN	LOPES 3:1 OR	STEEPER.					
E OR THE OWNER IF DEEME R SITE IS STABILIZED, REM AS, AND INSTALL PERMANEN	OVE ALL TEMPO	DRARY MEASURES, FINE G					L
TÁIN PERMANENT VEGETATI RY 6 MONTHS UNTIL COMPLI IN 6" OF FINAL GRADE, RE-	ON BY TOP DRI ETION OF THE I	ESSING WITH 700 LBS PE PROJECT.					
GRADE, PERMANENTLY SEE DVE ALL REMAINING TEMPOR PLETION AND STABILIZATION	D AND MULCH RARY EROSION	ALL-LANDSCAPED AREAS					
PERMANENT SEEDING							
IN ROADWAY AREAS: MARCH 1 – AUGUST 31:							К
<u>SEED MIX:</u> TALL FESCUE CENTIPEDE			<u>RATE:</u> 50 LB/AC 10 LB/AC				
BERMUDAGRASS (HULL SOIL AMENDMENTS:	,		25 LB/AC RATE:				
FERTILIZER (10-20-20 LIMESTONE))		500 LB/AC 4000 LB/AC				
<u>september 1 – februa</u> <u>seed mix:</u> TALL FESCUE	RY 28:		<u>rate:</u> 50 LB/AC				
CENTIPEDE BERMUDAGRASS (UNHI	JLLED)		10 LB/AC 35 LB/AC				ſ
<u>SOIL AMENDMENTS:</u> FERTILIZER (10-20-20 LIMESTONE))		<u>RATE:</u> 500 LB/AC 4000 LB/AC				
IN WASTE/BORROW AREAS:							
MARCH 1 – AUGUST 31: SEED MIX: TALL FESCUE			RATE: 75 LB/AC				
BERMUDAGRASS (HULL SOIL AMENDMENTS: FERTULZER (10-20-20	,		25 LB/AC <u>RATE:</u> 500 LB/AC				Н
FERTILIZER (10-20-20 LIMESTONE	, ,		500 LB/AC 4000 LB/AC				
<u>SEPTEMBER 1 – FEBRUA SEED MIX:</u> TALL FESCUE BERMUDAGRASS (UNHI			<u>RATE:</u> 75 LB/AC 35 LB/AC				
SOIL AMENDMENTS: FERTILIZER (10-20-20			<u>RATE:</u> 500 LB/AC				
LIMESTONE MULCH:	5)		4000 LB/AC				G
APPLY 4,000 LB/ACRI ANOTHER SUITABLE MU ROVING, NETTING, OR	JLCH. ANCHOF By crimping w	/ OR EQUIVALENT COVER R BY TACKING WITH ASPH (ITH A MULCH ANCHORING	IALT, G TOOL. A				
DISK WITH BLADES SE ANCHORING TOOL.	T NEARLY STRA	NGHT CAN BE USED AS A	A MULCH				
MAINTENANCE: REFERTILIZE THE FOLL REPEAT AS GROWTH R	OWING APRIL W EQUIRES. MAY	'ITH 50 LB/ACRE NITROGE ' BE MOWED AS OFTEN A	EN. S NEEDED.				
NOTE: SEE NCDOT'S LATES INFORMATION.	T STANDARDS	FOR STABILIZATION FOR I	MORE				F
PERMANENT SEEDBED			S BEFORE				
MPLETE GRADING ACCORDIN IZER NEEDS SHOULD BE DE OF CHARGE BY THE NC DI			GIS				
PLE CARTONS, AND INFORM S OR FROM NCDA. BECAU DE TURN-AROUND, SAMPLII	ATION ARE AVA JSE THE NCDA	ILABLE THROUGH COUNT SOIL TESTING LAB REQUI	Y AGRICULTURAL RES 1—6				
IG IS ALSO DONE BY COMM S ARE NOT AVAILABLE, FOL	ERCIAL LABORA	TORIES.					_
IS SHEET. APPLICATION RA			G RANGES:				E
TEXTURED, SANDY SOILS: TEXTURED, CLAYEY SOILS:	1 – 1.5 TONS/ 2 – 3 TONS,	ACRE /ACRE					
: ES: 800 – 1200 LB/ACRE -LEGUME MIXTURES: 800			JIVALENT)				
FERTILIZER EVENLY AND IN R SUITABLE MEANS. OPER			S OF SOIL BY				
CES IN ACCORDANCE WITH BED PREPARATION BY BREA	king up large	CLODS AND RAKING INT	O A SMOOTH,	NO	REVISION	DATE	D
E (SLOPES LESS THAN 3:1. AST SEED INTO A FRESHLY) FILL IN OR L LOOSENED SEE	LEVEL DEPRESSIONS THAT EDBED THAT HAS NOT BE	I CAN COLLECT EN SEALED BY	SEAL	TH CARO		
NEW STABILIZ	ATION TIMEF	RAMES			ON ESSION 14		
DESCRIPTION	STABILIZATION	TIMEFRAME EX			1232471		
WALES, DITCHES, SLOPES	7 DAYS	NOT STEEPER THAN 2:1, 14	4 DAYS ARE ALLOWED		HEN JANNIN	ARCHITECTU	JRE c
R (HQW) ZONES	7 DAYS	7 DAYS FOR SLOPES GREATE		625 LYN	NNDALE CT., SUITE F, GREE	ENVILLE, NC 27858 252-35	5-1068
rer	7 DAYS						
TH SLOPES FLATTER THAN 4:1		Project #2023011 NONE				IUNICATIONS QUARTERS	
	14 DAYS			DRAWING		AMPSON COUNT- NO	В
						CONTROL	
					NOTES	-NCGO1	
		₩ K]	& ASSOCIATES, INC	C. DRAWN	AS SHOWN	DRAWING NO	
		versandassocia Forks Place III Ste. 23	tes.com Since 191	18	MS	_	
	353 Ral	3 E. Six Forks Road eigh, NC 27609 9.594.1626	Planne: Surveyoi	rs DATE	JSJ	C 6.2	A
	EDA	INVESTMENT NO. 04-01-074		PROJECT N	07-15-2023 ••• 202311		-
	SCO	# 19-20081-01A; NCCCS #	2436	© COPYRIC	202311 GHT, JKF ARCHITECTURE PC, JOHN	K. FARKAS, AIA	


14





1		

DU	LE				
DDE	BOTANICAL / COMMON NAME	CONTAINER	CALIPER	SIZE	QTY
CK	Cladrastis kentukea / American Yellowwood	В&В	3" CAL.	14` - 16` HT.	3
٧S	Nyssa Sylvatica / Black Gum	В&В	3" CAL.	14` - 16` HT.	3
QΡ	Quercus phellos `Hightower` / Willow Oak	В&В	3" CAL.	14` - 16` HT.	11
ΩR	Quercus shumardii / Shumard Red Oak	В&В	3" CAL.	14` - 16` HT.	4
ΓD	Taxodium distichum / Bald Cypress	В&В	3" CAL.	14` - 16` HT.	5
DDE	BOTANICAL / COMMON NAME	CONTAINER	CALIPER	SIZE	QTY
CV	Chionanthus virginicus / White Fringetree	15 gal	2" CAL.	8`-12` HT.	9
ЛV	Magnolia virginiana / Sweet Bay Magnolia	15 gal	2" CAL.	8`-12` HT.	7



RAI Project #2023011



OPYRIGHT, JKF ARCHITECTURE PC, JOHN K. FARKAS, AIA

0 20' 40'

SCALE 1 inch = ft

K J G F	
K J G F	
H G F	
H G F	
G F	
G F	
G F	
F	
F	
A CALL BEFORE YOU DIG! WWW.NC811.ORG N.C. ONE-CALL CENTER IT'S THE LAW!	
1 2 3 4 5	

NOTES:	
 ALL TREES ARE TO BE NURSERY GROWN, BAL BURLAP (B&B) OR CONTAINER GROWN. 	L AND
 REMOVE ALL TREATED OR PLASTIC-COATED BURLAP, STRAPPING WIRE OR NYLON TWINE F ROOTBALL. AFTER SETTING IN HOLE, CUT AWA AND SIDES OF WIRE BASKET, IF ANY. 	
 INSTALL TOP OF PLANT BALL EVEN 2-3" ABOVE EXISTING GRADE. 	
 TAMP PLANTING MIX FIRMLY AS PIT IS FILLED AROUND EACH PLANT BALL. 	ROOT
5. SOAK ROOT BALL AND PLANT PIT IMMEDIATEL' AFTER INSTALLATION.	
6. SET TREE IN VERTICAL POSITION & STAKE IF / NEEDED	AS
7. SUBMIT PREFERRED STAKING METHODS IF/AS NEEDED AND MATERIALS TO LANDSCAPE ARCHITECT FOR APPROVAL	4" HI BERM C
 ALL STAKING TO BE REMOVED AFTER ONE YEA GROWING SEASON 	AR
 REMOVE EXCESS SOIL FROM SITE AND DISPOSIN A LEGAL MANNER. 	SE OF
10.RESEED UNMULCHED, DISTURBED AREAS. 11. MULCH AREA TO BE A MINIMUM 2' RADIUS FRO TREE TRUNK.	DM —
12. SEE SPECS FOR ADDITIONAL PLANTING INFORMATION	REM SOI
	REMOVE TOP 1/3 BURLAP AND
	REMOVE TOP 1/3 OF WIRE BAS
AT ⁻	RAISE PIT BOTTOM
ALL TF	REES SHALL MEET AMERIC
FOR EXAMPLE:	
_	2" 12-14' 3" 14-16' 4" 16-18'
🦳 TREE PLAN	TING
NOTEO	
NOTES:	
NOTES: 1. SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL.	PLANT
1. SCARIFY ROOT MASS OF CONTAINERIZED	
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC 	VE
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI 	VE ED 2" LAYER OF TRIPI N AGED HARDV
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. 	VE ED 2" LAYER OF TRIP N AGED HARD\ KEEP 3" FRO
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. 	VE ED 2" LAYER OF TRIP N AGED HARD\ KEEP 3" FRO
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA 	VE ED 2" LAYER OF TRIP N AGED HARD KEEP 3" FRO TELY
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA 	VE ED 2" LAYER OF TRIP N AGED HARD KEEP 3" FRO TELY
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA 	VE ED 2" LAYER OF TRIP N AGED HARD KEEP 3" FRO TELY
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA 	VE ED 2" LAYER OF TRIP N AGED HARD KEEP 3" FRO TELY
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA 	VE ED 2" LAYER OF TRIP N AGED HARD KEEP 3" FRO TELY
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA AFTER INSTALLATION. 	VE ED 2" LAYER OF TRIP N AGED HARD KEEP 3" FRO TELY
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIAT AFTER INSTALLATION. 	VE ED 2" LAYER OF TRIPI N AGED HARDV KEEP 3" FRO TELY AF
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIA AFTER INSTALLATION. 	VE ED N 2" LAYER OF TRIP AGED HARDA KEEP 3" FRO TELY AF
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIAT AFTER INSTALLATION. 	VE ED N 2" LAYER OF TRIPI AGED HARDV KEEP 3" FRO TELY AF
 1. SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. 2. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. 3. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. 4. OMIT COLLAR AROUND EACH SHRUB WHEI IRRIGATION SYSTEM IS PRESENT. 5. SOAK EACH PLANT BALL AND PIT IMMEDIAT AFTER INSTALLATION. 	VE ED 2" LAYER OF TRIPI AGED HARDV KEEP 3" FRO TELY AF
 SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. OMIT COLLAR AROUND EACH SHRUB WHEIRRIGATION SYSTEM IS PRESENT. SOAK EACH PLANT BALL AND PIT IMMEDIAT AFTER INSTALLATION. CROWN HEIGHT IN INCHES EQUALS WIDTH IN FEET TO 12" MAX. 10" (EX.) 10" (EX.) 10" (EX.)	VE ED 2" LAYER OF TRIPI AGED HARDV KEEP 3" FRO TELY AF FINAL GRADE EXISTING GRA EX.) CROWNING
 1. SCARIFY ROOT MASS OF CONTAINERIZED MATERIAL. 2. INSTALL CONTAINERIZED PLANTS 2-3" ABC FINISHED GRADE. 3. TAMP PLANTING MIX FIRMLY AS PIT IS FILL AROUND EACH PLANT BALL. 4. OMIT COLLAR AROUND EACH SHRUB WHEN IRRIGATION SYSTEM IS PRESENT. 5. SOAK EACH PLANT BALL AND PIT IMMEDIATAFTER INSTALLATION. 	VE ED N 2" LAYER OF TRIPI AGED HARDV KEEP 3" FRO TELY AF EX.) FINAL GRADE EXISTING GRA EX.) CROWNING

10

8

9

6

7

NOTES:

- BOUNDARY AND TOPOGRAPHIC SURVEY PROVIDED BY ATLANTIC SURVEYING, P.A.
 CONTRACTOR SHALL FIELD VERIFY LOCATION, SIZE, AND MATERIAL OF EXISTING SITE AND VICINITY FEATURES AND UTILITIES PRIOR TO BEGINNING DEMOLITION AND CONSTRUCTION ACTIVITIES. CONTRACTOR SHALL NOTIFY THE CIVIL ENGINEER AND LANDSCAPE ARCHITECT OF ANY DISCREPANCIES THAT ARE FOUND BETWEEN THE EXISTING FIELD CONDITIONS AND THE SITE PLANS OR CONSTRUCTION DRAWINGS, WHENEVER THEY ARE FOUND, DURING ALL PHASES OF SITE WORK.
- 3. THE PRUNING OF SCREENING SHRUBS SHALL ALLOW FOR LATERAL GROWTH OF BRANCHES SO AS TO FORM A HEDGE.
- 4. ALL LANDSCAPE ISLANDS, BEDS AND LAWNS SHALL BE GRADED FOR POSITIVE DRAINAGE WITH NO LOW SPOTS ALLOWING WATER TO BE TRAPPED.
- CONTRACTOR SHALL PLANT TREES AND SHRUBS 5 FEET FROM BACK OF CURB WHEN PLANTED PERPENDICULAR FROM PARKING SPACES.
 WHEEL STOPS ARE REQUIRED IF LANDSCAPING CANNOT BE SET BACK 5 FEET.
- WHEEL STOPS ARE REQUIRED IF LANDSCAPING CANNOT BE SET BACK 5 FEE
 CONTRACTOR SHALL INSTALL ALL SHRUBS IN MULCHED BEDS.
- CONTRACTOR SHALL INSTALL ALL TREES IN MINIMUM 4'-6' DIA. MULCHED BEDS OF 3-4" DEPTH.
 WHERE TREES AND SHRUBS ARE LOCATED TOGETHER IN LANDSCAPE BUFFERS, THE
- CONTRACTOR SHALL MULCH THE FULL WIDTH AND LENGTH OF THE BUFFER.
 10. ALL UN-MULCHED AREAS OF THE SITE SHALL BE SODDED OR SEEDED WITH LAWN GRASS.
- SEE PLAN FOR SOD/SEED LOCATIONS. GRASS SEED SELECTION SHALL BE SUBMITTED TO AND APPROVED BY THE LANDSCAPE ARCHITECT, PRIOR TO PURCHASE AND INSTALLATION.11. SEE SPECS FOR ADDITIONAL INFORMATION.

